





Concealed Steel Hinge - Model #303

Finish

Satin Brass Satin Chrome

DESCRIPTION

The hinge is invisible when closed.

Richelieu's concealed hinges offer superior appearance and durability with contemporary and functional style. They easily install and can be used for many applications on wood or metal doors to meet all your needs.

ADVANTAGES AND BENEFITS

Security: When closed, the SOSS concealed hinge cannot be seen or tampered with. When opened, the riveted hinge pin is non-removable. Safety: The moving pivot point remains inside the hinge during movement until fully opened, eliminating an external pinch point on the back side of the door. Strength: The installed hinge is firmly anchored in a deep, full mortise with screws to support the door and provide a rigid and secure installation. Superior Construction: Concealed hinges are designed to ensure reliable operation for years. The standard hinges are made of high-strength steel and zinc alloy. Smooth Operation: All hinges have been designed and developed to give smooth performance and reduce friction.

AVAILABLE PRODUCTS

Product #	Finish
420303160	Satin Brass
420303145	Satin Chrome



TECHNICAL SPECIFICATIONS

Minimum Door Thickness11/16 inMaterialSteelType of HingeWood or MetalFor Hinge #303Wood Screw Sizes#5 x 3/4" (3.5 mm x 19 mm)Center to Center (mm)1 inDoor/Jamb Gap (mm)1/8 inDoor/Jamb Inset (mm)3/8 inScrew/NallScrew/Nail (Included)Fixing TypeMortiseGabinet Angle180°Vidth1/2 inLeaf Gap3/8 inDoor/Jamb Inset (mm)3/8 inGabinet Angle180°Hight1/2 inLeaf Gap1/8 inDoor/Jamb Inset1/8 inLeaf Body Mortise Length1/8 inDoor/Jamb Inset1/8 inLeaf Body Mortise Length1/8 inLeaf Mortise Depth1/82 inHight2/8 inHight2/8 inHight2/8 inHight1/8/8 in		
Type of HingeWood or MetalFor Hinge #303Wood Screw Sizes#5 x 3/4" (3.5 mm x 19 mm)Center to Center (mm)1 inDoor/Jamb Gap (mm)1/8 inDoor/Jamb Inset (mm)3/8 inScrew/NailScrew/Nail (Included)Fixing TypeScrew-OnMounting TypeMortiseCabinet Angle180°Vidth1/2 inLeaf Gap3/8 inDoor/Jamb Inset133/64 inDoor/Jamb Inset1/8 inDoor/Jamb Gap (mm)1/8 inLeaf Body Mortise Length1/8 inDoor/Jamb Inset1/8 inLeaf Body Mortise Length1/9/32 inLeaf Body Mortise Length1/32 inLeaf Mortise Depth3/64 inHaddenessReversible	Minimum Door Thickness	11/16 in
For Hinge #303Wood Screw Sizes#5 x 3/4" (3.5 mm x 19 mm)Center to Center (mm)1 inDoor/Jamb Gap (mm)1/8 inDoor/Jamb Inset (mm)3/8 inScrew/NailScrew/Nail (Included)Fixing TypeScrew-OnMounting TypeMortiseCabinet Angle1/2 inLeaf Gap3/8 inDoor/Jamb Inset1/3/64 inDoor/Jamb Gap in Closed Position1/32 inLeaf Body Mortise Length1/32 inLeaf Mortise Depth3/64 inKeversible1/64 in	Material	Steel
Wood Screw Sizes#5 x 3/4" (3.5 mm x 19 mm)Center to Center (mm)1 inDoor/Jamb Gap (mm)1/8 inDoor/Jamb Inset (mm)3/8 inScrew/NailScrew/Nail (Included)Fixing TypeScrew/OnMounting TypeMortiseCabinet Angle180°Vidth1/2 inLeaf Gap3/8 inDoor/Jamb Gap (mom)1/8 inDoor/Jamb Gap1/8 inDoor/Jamb Gap1/8 inDoor/Jamb Gap in Closed Position1/32 inHeight4/64 inLeaf Mortise Depth3/64 inHeight8/64 inHeight8/64 inLeaf Mortise Depth8/64 in	Type of Hinge	Wood or Metal
Center to Center (mm)1 inDoor/Jamb Gap (mm)1/8 inDoor/Jamb Inset (mm)3/8 inScrew/NailScrew/Nail (Included)Fixing TypeScrew-OnMounting TypeMortiseCabinet Angle180°Width1/2 inLeaf Gap3/8 inDoor/Jamb Inset1/8 inDoor/Jamb Gap1/8 inDoor/Jamb Gap1/8 inDoor/Jamb Inset1/932 inHeight1/32 inHeight3/64 inHeight8/04 inHeight1/04 inHeight1/04 in	For Hinge #	303
Door/Jamb Gap (mm)1/8 inDoor/Jamb Inset (mm)3/8 inScrew/NailScrew/Nail (Included)Fixing TypeScrew-OnMounting TypeMortiseCabinet Angle180°Width1/2 inLeaf Gap3/8 inDoor/Jamb Gap1/8 inDoor/Jamb Inset1/8 inDoor/Jamb Gap1/8 inDoor/Jamb Inset1/8 inLeaf Body Mortise Length19/32 inHeight41/64 inLeaf Mortise Depth3/64 inReversible3/64 in	Wood Screw Sizes	#5 x 3/4" (3.5 mm x 19 mm)
Door/Jamb Inset (mm)3/8 inScrew/NailScrew/Nail (Included)Fixing TypeScrew-OnMounting TypeMortiseCabinet Angle180°Vidth1/2 inLeaf Gap3/8 inLength1 33/64 inDoor/Jamb Gap1/8 inLeaf Body Mortise Length1/9/32 inDoor/Jamb Gap in Closed Position1/32 inHeight41/64 inHeight8Leaf Mortise Depth8Kersible1000000000000000000000000000000000000	Center to Center (mm)	1 in
Screw/NailScrew/Nail (Included)Fixing TypeScrew/OnMounting TypeMortiseCabinet AngleI80°Vidth1/2 inLeaf Gap3/8 inLength1 33/64 inDoor/Jamb Gap1/8 inLeaf Body Mortise Length1/932 inLeaf Body Mortise Length3/64 inLeaf Mortise Depth3/64 inKeyersibleScrew/Data	Door/Jamb Gap (mm)	1/8 in
Fixing TypeScrew-OnMounting TypeMortiseCabinet Angle180°Vidth1/2 inLeaf Gap3/8 inLength1 33/64 inDoor/Jamb Gap1/8 inLeaf Body Mortise Length19/32 inDoor/Jamb Gap in Closed Position1/32 inHeight41/64 inLeaf Mortise Depth3/64 in	Door/Jamb Inset (mm)	3/8 in
Mounting TypeMortiseCabinet Angle180°Width1/2 inLeaf Gap3/8 inLength1 33/64 inDoor/Jamb Gap1/8 inLeaf Body Mortise Length19/32 inLeaf Body Mortise Length1/32 inLeaf Mortise Depth3/64 inKeyrsible8eversible	Screw/Nail	Screw/Nail (Included)
Cabinet Angle180°Width1/2 inLeaf Gap3/8 inLength1 33/64 inDoor/Jamb Gap1/8 inDoor/Jamb Inset1/8 inLeaf Body Mortise Length19/32 inDoor/Jamb Gap in Closed Position1/32 inHeight41/64 inLeaf Mortise Depth3/64 inHandednessReversible	Fixing Type	Screw-On
Width1/2 inLeaf Gap3/8 inLength1 33/64 inDoor/Jamb Gap1/8 inDoor/Jamb Inset1/8 inLeaf Body Mortise Length19/32 inDoor/Jamb Gap in Closed Position1/32 inHeight41/64 inLeaf Mortise Depth3/64 inReversibleReversible	Mounting Type	Mortise
Leaf Gap3/8 inLength1 33/64 inDoor/Jamb Gap1/8 inDoor/Jamb Inset1/8 inLeaf Body Mortise Length19/32 inDoor/Jamb Gap in Closed Position1/32 inHeight41/64 inLeaf Mortise Depth3/64 inHandednessReversible	Cabinet Angle	180°
Length1 33/64 inDoor/Jamb Gap1/8 inDoor/Jamb Inset1/8 inLeaf Body Mortise Length19/32 inDoor/Jamb Gap in Closed Position1/32 inHeight41/64 inLeaf Mortise Depth3/64 inReversibleReversible	Width	1/2 in
Door/Jamb Gap1/8 inDoor/Jamb Inset1/8 inLeaf Body Mortise Length19/32 inDoor/Jamb Gap in Closed Position1/32 inHeight41/64 inLeaf Mortise Depth3/64 inHandednessReversible	Leaf Gap	3/8 in
Door/Jamb Inset1/8 inLeaf Body Mortise Length19/32 inDoor/Jamb Gap in Closed Position1/32 inHeight41/64 inLeaf Mortise Depth3/64 inHandednessReversible	Length	1 33/64 in
Leaf Body Mortise Length19/32 inDoor/Jamb Gap in Closed Position1/32 inHeight41/64 inLeaf Mortise Depth3/64 inHandednessReversible	Door/Jamb Gap	1/8 in
Door/Jamb Gap in Closed Position1/32 inHeight41/64 inLeaf Mortise Depth3/64 inHandednessReversible	Door/Jamb Inset	1/8 in
Height 41/64 in Leaf Mortise Depth 3/64 in Handedness Reversible	Leaf Body Mortise Length	19/32 in
Leaf Mortise Depth 3/64 in Handedness Reversible	Door/Jamb Gap in Closed Position	1/32 in
Handedness Reversible	Height	41/64 in
	Leaf Mortise Depth	3/64 in
Hinge Opening Angle +180°	Handedness	Reversible
	Hinge Opening Angle	+180°

APPLICATION

The concealed hinges are used by designers, architects, and engineers to help solve design problems associated with today's ultra modern materials. Our hinges are found in many applications where concealment, compact size, and smooth operation are essential. Concealed hinges can be found in various high-tech products including, computers, cash registers, copy machines, medical equipment, and office equipment. Limited only by the imagination of the designer, SOSS concealed hinges are used in Cessna Bravo jets, custom furniture by experts in the cabinet and display industry and wherever invisibility and flexibility are of paramount importance. SOSS concealed hinges open a full 180° and operate with a single action. Ideally suited for mirrored doors, gates, wall panels, pass doors, storage cabinets, electronic and computer devices, wall units, hidden doors, pharmaceutical storage areas, courtrooms, and churches. SOSS concealed hinges are used in restaurants, homes, and offices to create environments with clean lines.

IMPORTANT INFORMATION

Note: Picture for visual reference only: actual product may vary from that shown in photo. Always use the instructions inside the packaging provided by the manufacturer, as the manufacturer reserves the right to make technical changes or modify information without prior notice! Always make sure to fix properly the product using the right fixation for the proper material. Never exceed the maximum weight or the maximum dimension recommended by the manufacturer. Never use any spray lubricant on these products.



DISCLAIMER

The preceding information, as well as any technical recommendations given in writing, verbally, or based on tests, is provided to the best of our knowledge. However, recommendations are non-binding and do not affect your responsibility to determine the correctness of the given recommendations and the suitability of the product for your particular purposes. The application, use, or processing of our products, as well as the production of products based on our technical recommendations, are out of our control and therefore fall exclusively under your responsibility. Sales of our products are subject to our most recent General Sales and Delivery Conditions. Please note that Richelieu will not accept any returns or claims for unpackaged products. Warning: This product can expose you to chemicals including chromium and nickel, which are known to the State of California to cause cancer or other reproductive harm. For further information go to www.p65warnings.ca.gov.

PRODUCT PHOTOS











