



## TRESCO Infinex Extrusion

### Mounting



### Length

72 in

94 in

### Height

5/16 in

5/16 in\*

15/32 in\*

1/2 in


1/2 in\*

9/16 in

11/16 in

23/32 in\*

### Finish



Black



Satin Clear

### Shape

Angle

Curve

Recess

Rectangle

Round

Square

### Packaging format

Per unit

Length

## DESCRIPTION

### Five unique profiles to choose from

Infinex is the innovative, patent-pending LED aluminum extrusion system. Gone are the days of set fixture sizes -- simply choose your style, cut to desired length and assemble to create a customized LED fixture. Designed by our in-house engineers and made in the USA, Infinex carries a UL safety certification and is available in five profiles with an array of installation options.

Infinex is designed for easy DIY application

## ADVANTAGES AND BENEFITS

For FlexTape options see the 12VDC Flexible section. FlexTape slides into proprietary

power feed end cap

## AVAILABLE PRODUCTS

Product #	Mounting	Length	Height	Finish	Shape	Packaging format
<b>LXREC72SC10</b>	Recessed	72 in	5/16 in	Satin Clear	Recess	Per unit
<b>LXREC72BL</b>	Recessed	72 in	5/16 in*	Black	Rectangle	Length
<b>LXREC94SC</b>	Recessed	94 in	5/16 in	Satin Clear	Recess	Per unit
<b>LXSQR72BL</b>	Surface	72 in	15/32 in*	Black	Square	Length
<b>LXCRV72SC10</b>	Surface	72 in	1/2 in	Satin Clear	Curve	Per unit
<b>LXSQR72SC10</b>	Surface	72 in	1/2 in	Satin Clear	Square	Per unit
<b>LXCRV72BL</b>	Surface	72 in	1/2 in*	Black	Curve	Length
<b>LXANG72SC10</b>	Surface	72 in	9/16 in	Satin Clear	Angle	Per unit
<b>LXRND72SC10</b>	Surface	72 in	11/16 in	Satin Clear	Round	Per unit
<b>LXRND72BL</b>	Surface	72 in	23/32 in*	Black	Round	Length

## TECHNICAL SPECIFICATIONS

<b>Luminaire</b>	Rigid Linear
<b>Location</b>	Under Cabinet, Closet, Furniture
<b>Application</b>	Kitchen, Bedroom, Office
<b>Lighting</b>	Ambience, Accent
<b>Material</b>	Aluminum
<b>Function</b>	Aluminum Profile
<b>Lighting Type</b>	LED
<b>Style</b>	Contemporary, Functional
<b>Tension (V)</b>	12 V

### Disclaimer

Measures shown with an asterisk (\*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

## IMPORTANT INFORMATION

Cut to size. Aluminum extrusions can be cut on a variety of equipment. For the best performance and longest life, use a saw blade designed for nonferrous, thin stock, on your miter saw. It is also highly recommended to cut the extrusion with a diffuser securely attached via clamps, tape, stretch wrap, etc. to prevent unwanted cracking of diffuser. The diffusers are not included. Please add products: LX72DIFFMLK or LX72DIFFR10 or LX72DIFFCL10

## DISCLAIMER

Also offered on special order prefabricated custom solutions with a minimum quantity order; please speak with your Richelieu Sale Representative All product dimensions and specifications are subject to change without prior notice.

## PRODUCT PHOTOS



► Five unique profiles to choose from