



## Designer Flap Stay for Wood Cabinet Door

### Packaging Specifications

Not Applicable	UPC Code / Plastic Bag
----------------	------------------------

### Finish

Aluminium	Chrome
-----------	--------

### DESCRIPTION

#### For up-opening OR down-opening doors

Up-opening doors: stays open at 75°, 90° and 100°.  
Down-opening doors: stays open at 90° only.  
Tension-adjustable using an Allen key (included)  
For wood doors between 300 and 500 mm long.  
Wide operating range: refer to chart for details.  
Uses very little place within the cabinet.  
Minimum required installation depth: 140 mm  
Lateral space used: 20 mm

### ADVANTAGES AND BENEFITS

- Approved ANSI / BIFMA - 3 opening angles

### AVAILABLE PRODUCTS

Product #	Packaging Specifications	Finish
65130145	Not Applicable	Aluminium
65130180	Not Applicable	Chrome
BP65130180	UPC Code / Plastic Bag	Chrome

## TECHNICAL SPECIFICATIONS

Standards and Certifications	ANSI/BIFMA
Screw/Nail	Included
Length	9 1/16 in*
Door Length	11 3/4 to 19 5/8 in*
Opening Angle Adjustability	75°-100°
Side	Reversible
Door Type	Wood Doors
System Type	Duo
Material	Steel
Door Height	11 3/4 to 35 3/8 in*

### Disclaimer

Measures shown with an asterisk (\*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

## APPLICATION

Wood doors

## INCLUDED PRODUCT(S)

1 Stay 1 door attachment 1 cabinet attachment 1 Allen key 4 wood screws to anchor the door and cabinet attachments

## IMPORTANT INFORMATION

For doors over 500 mm wide (whatever their weight), use two stays.

## PRODUCT PHOTOS

---

