



Industrial Black Phenolic Casters

Load Capacity Per Caster

Max. 573 lb* Max. 772 lb*

Wheel Diameter



Total Height



Tread Width



Fastening Type



Axle Diameter



Axle Length



Features



DESCRIPTION

Non-marking rubber tread

These heavy-duty industrial black phenolic casters are suitable for extreme cold and extreme heat conditions. Available in fixed, swivel, or swivel with brake.

ADVANTAGES AND BENEFITS

- Non-marking, non-conductive, and spark-proof - High strength, high impact, resistance to oil, gasoline, and dilute acids - Carbon steel top plate, heat-treated for



extra strength - Lubrication fitting for swivel raceway and wheel bearings

AVAILABLE PRODUCTS

Product #	Load Capacity Per Caster	Wheel Diameter	Total Height	Tread Width	Fastening Type	Axle Diameter	Axle Length	Features
F26820	Max. 573 lb*	3 15/16 in*	5 5/16 in*	1 31/32 in*	Swivel with Brake	25/32 in*	2 3/8 in*	With Lubrication Fittings
F26819	Max. 573 lb*	3 15/16 in*	5 5/16 in*	1 31/32 in*	Swivel Without Brake	25/32 in*	2 3/8 in*	With Lubrication Fittings
F27116	Max. 772 lb*	5 31/32 in*	7 5/16 in*	1 25/32 in*	Fixed	5/8 in*	1 31/32 in*	Without Lubrication Fittings
F26817	Max. 772 lb*	5 31/32 in*	7 5/16 in*	1 25/32 in*	Swivel Without Brake	5/8 in*	1 31/32 in*	With Lubrication Fittings

TECHNICAL SPECIFICATIONS

Mounting Type	Plate				
Material	Phenolic				
Recommended Surfaces	Concrete, Carpet, Wood/Planking, Asphalt				
Finish	Black				
Mounting Hole Diameter	7/16 in*				
Mounting Plate Dimensions	31 5/16 in x 4 1/2 in (100 mm x 115 mm)				
Conditions	Extreme Cold, Extreme Heat, Petroleum Products, Dilute Acids				

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, <u>click here</u>.

IMPORTANT INFORMATION

For all additional measurements, please see the technical documents

DISCLAIMER

Technical data subject to change without prior notice.



PRODUCT PHOTOS

