



## Cinetto PS48 Bypassing Sliding Door System

### Door Thickness

23/32 in\*

3/4 to 29/32 in\*

15/16 to 1 5/16 in\*

### Number of Doors

2

3

### Door Width

23 5/8 to 60 in\*

23 5/8 to 70 7/8 in\*

25 5/8 to 60 in\*

25 5/8 to 70 7/8 in\*

### Cabinet Width

47 1/4 to 120 in\*

70 7/8 to 213 in\*

76 3/4 to 213 in\*

## DESCRIPTION

### For large and heavy cabinet doors

The Cinetto PS48 Bypassing Sliding Door System is designed for large and heavy cabinet doors weighing up to 176 lb (80 kg) each.

- For a variety of door thicknesses from 11/16 in to 1-1/4 in (18 mm to 33 mm), or special order for thicker doors up to 2" (53 mm)
- Versatile system for a variety of door configurations: for 1, 2, 3, 4, and multiple doors
- Simple installation with surface-mount tracks and adjustable hardware
- Integrated self-closing mechanism sold separately
- B-moved electronic motor system sold separately

The PS48 is an ideal solution for:

- Wardrobes and Armoires
- Kitchen Pantries
- Office Storage
- Entertainment Units

## AVAILABLE PRODUCTS

Product #	Door Thickness	Number of Doors	Door Width	Cabinet Width
<b>WEBKIT1214588</b>	23/32 in*	2	23 5/8 to 60 in*	47 1/4 to 120 in*
<b>WEBKIT1214591</b>	23/32 in*	3	23 5/8 to 70 7/8 in*	70 7/8 to 213 in*
<b>WEBKIT1214589</b>	3/4 to 29/32 in*	2	23 5/8 to 60 in*	47 1/4 to 120 in*
<b>WEBKIT1214592</b>	3/4 to 29/32 in*	3	23 5/8 to 70 7/8 in*	70 7/8 to 213 in*
<b>WEBKIT1214590</b>	15/16 to 1 5/16 in*	2	25 5/8 to 60 in*	47 1/4 to 120 in*
<b>WEBKIT1214593</b>	15/16 to 1 5/16 in*	3	25 5/8 to 70 7/8 in*	76 3/4 to 213 in*

## TECHNICAL SPECIFICATIONS

Door Material	Wood
Door Movement	Straight Sliding
Detailed Door Movement	Bypassing
Load Capacity	66.1 to 176 lb*
Door Position	Full Overlay
Application	Wardrobe, Pantry, Cabinet, Storage
Brand	CINETTO
Door Height	47 1/4 to 118 in*
Adjustable	Yes
Soft-Closing	Sold Separately
Displayed in These Showrooms	Mississauga
Brand Model	Cinetto PS48

### Disclaimer

Measures shown with an asterisk (\*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

## IMPORTANT INFORMATION

- Pictures provided for visual reference only: actual product may vary. - All required hardware should be ordered and obtained prior to initiating fabrication or installation work. Please verify that the parts and quantities listed in your order are correct before proceeding to checkout. - Always use instructions provided by the manufacturer, as included with the product. Manufacturer reserves the right to amend, modify, or otherwise supplement any previously issued product and/or technical information, as deemed required from time to time, without prior notice. - The documentation, drawings, and instructions on this page apply to the system described on this page only. Richelieu expressly declines all responsibility for any design or construction that combines this system with systems from this same manufacturer or systems from other manufacturers. - Installation of the product shall be executed by qualified individuals only, always ensuring that each product is securely installed using proper fixation methods, as appropriate for each applicable substratum. We trust that anyone installing these products has the required skills, knowledge, and experience. Richelieu expressly disclaims any liabilities for results obtained through improper use or installation. - Always remove debris/dust/residues (sawdust and/or aluminum) from all tracks and guide channels using a dry cloth during installation and before operating the system. - Never spray lubricant.

## INCLUDED PRODUCT(S)

We strongly recommend that you order the TUBECART and CAP (two CAPs per TUBECART) products to package this product.

## DISCLAIMER

By accessing or referring to this document, or by using any of Richelieu's websites, you accept all applicable terms as they apply from time to time. This legal disclaimer is in no way limited or altered by any other terms or conditions. Richelieu may change said terms at its discretion and without prior notice. A version of the most current terms will always be available on Richelieu's website. The preceding information and technical documentation, information, or recommendations issued by Richelieu verbally or in writing is believed to be accurate and is given in good faith, but no representation of warranty as to its completeness or accuracy is made. Suggestions for use or application are only opinions. Users are responsible for determining the suitability of these products for their own particular purpose. No representation of warranty, expressed or implied, is made with respect to information or products including, without limitation, warranties or merchantability, fitness for particular purpose, non-infringement of any third party patent or other intellectual property rights including, without limit, copyright, trademark, and designs. Any trademarks identified herein are trademarks of the Richelieu group of companies. Richelieu assumes no risk and shall not be subject to any liability for damages or loss resulting from the specific use or application made of the product. Richelieu's liability for any claim, whether based on breach of contract, negligence, or infringement of any rights of any party relating to the product shall not exceed the price paid for said products. In no event shall Richelieu be liable for any special, incidental, or consequential damages (including loss of use, loss of profit, and claims of third parties) however caused, whether by the negligence of Richelieu or otherwise. Products returned for warranty purposes shall be subject to Richelieu's then applicable Return Policy.

## PRODUCT PHOTOS

