



## Baluster Post with Base

### Baluster Post Size

ø 38.1 mm (1 1/2")

ø 50.8 mm (2")

## DESCRIPTION

### Floor Mounting

Baluster tubing can be inserted easily into the floor-mounted base. The base must be covered with a trim ring to conceal the installation screws.

## ADVANTAGES AND BENEFITS

Available in 304 grade finish for interior use and 316 grade for interior and exterior use.

## AVAILABLE PRODUCTS

Product #	Baluster Post Size
<a href="#">HR14091543812</a>	ø 38.1 mm (1 1/2")
<a href="#">HR14091545012</a>	ø 50.8 mm (2")

## TECHNICAL SPECIFICATIONS

Finish	Brushed Stainless Steel
Recommended Location Usage	Interior
Thickness	3/32 in*
Material	Stainless Steel 304
Height	38 in
Type of Mounting	Floor Mount
Category	Posts
Baluster Post Type	Round Tube

### Disclaimer

Measures shown with an asterisk (\*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

## INCLUDED PRODUCT(S)

Includes post and welded on mounting base, trim ring not included.

---

## IMPORTANT INFORMATION

Always set the product in a suitable material. Never use a spray lubricant on this product. Maintenance: clean with a soft cloth and non-abrasive soap or ammonia. This illustration is provided for visual reference only. Actual product may vary. Order hardware before starting the job. The manufacturer reserves the right to change product and information without notice. Always follow the instructions inside the package. Drawings and technical documents contain examples of hardware from different manufacturers. The customer may not in any case make a claim following the use of these documents. The company disclaims any responsibility for the structural details related to a construction or project. Installation must be done by qualified personnel. Always make sure that the product is properly installed using suitable fixtures on the support material. Never exceed the load or maximum size recommended by the manufacturer. Never use a spray lubricant on this product.

## DISCLAIMER

The preceding information as well as any technical recommendation given in writing, verbally or based on tests is provided to the best of our knowledge. However, recommendations are non-binding and do not diminish your responsibility for determining the correctness of these recommendations and the suitability of the product for your particular purpose. The application, use or processing of our products as well as the production of products based on our technical recommendations are beyond our control and therefore exclusively your responsibility. Sales of our products are subject to our most recent General Sales and Delivery Conditions. Please note that Richelieu will not accept any returns or claims for unpackaged products.

## PRODUCT PHOTOS

