



Krona Koblenz 7-Fulcrum Concealed Hinges

Minimum Door Thickness

1 3/8 in*

1 1/2 in*

1 9/16 in*

Finish

Polished
Chrome

Satin Chrome

Satin Nickel

Steel

Material


Stainless
Steel

Zinc Alloy
(Zamak)

Fire Resistant

30 minutes

Maximum Capacity (2 Hinges)

88.2 lb*

132 lb*

176 lb*

265 lb*

441 lb*

Maximum Capacity (3 Hinges)

110 lb*

132 lb*

220 lb*

309 lb*

Self-Closing

Self-Closing
Hinge

Drilling Depth (mm)

1 5/32 in*

2 17/32 in*

Center to Center (mm)

4 1/8 in*

5 1/2 in*

Door/Jamb Inset (mm)

1/8 in*

Standards and Certifications

Not Certified

UL / UL10C /
ULC

UL / UL10C /
ULC / CE

Cabinet Angle

180°

Width

1 3/16 in*

1 1/4 in*

2 15/16 in*

3 1/8 in*

Leaf Gap

19/32 in*

11/16 in*

Length

4 23/32 in*

6 5/16 in*

7 7/8 in*

9 1/16 in*

Door/Jamb Gap

1/8 in*

Door/Jamb Inset

5/32 in*

Leaf Body Mortise Length

4 23/32 in*

6 5/16 in*

Height

1 5/32 in*

1 7/32 in*

1 5/16 in*

2 17/32 in*

Leaf Mortise Depth

1 5/32 in*

2 17/32 in*

Packaging format

Box

Per unit

DESCRIPTION

Note: the 802000 Hinges Series has an adjustable self-closing speed.

AVAILABLE PRODUCTS

Product #	Minimum Door Thickness	Finish	Material	Fire Resistant	Maximum Capacity (2 Hinges)	Maximum Capacity (3 Hinges)	Self-Closing	Drilling Depth (mm)	Center to Center (mm)	Door/Jamb Inset (mm)	Standards and Certifications	Cabinet Angle	Width	Leaf Gap	Length	Door/Jamb Gap	Door/Jamb Inset	Leaf Body Mortise Length	Height	Leaf Mortise Depth	Packaging format
807000PC	1 3/8 in*	Polished Chrome	Zinc Alloy (Zamak)		88.2 lb*	110 lb*					UL / UL10C / ULC / CE										Per unit
807000SC	1 3/8 in*	Satin Chrome	Zinc Alloy (Zamak)		88.2 lb*	110 lb*					UL / UL10C / ULC / CE										Per unit
807000SN	1 3/8 in*	Satin Nickel	Zinc Alloy (Zamak)		88.2 lb*	110 lb*					UL / UL10C / ULC / CE										Per unit
808000SC	1 1/2 in*	Satin Chrome	Stainless Steel	30 minutes	132 lb*			1 5/32 in*	4 1/8 in*	1/8 in*	UL / UL10C / ULC	180°	3 1/8 in*	11/16 in*	4 23/32 in*	1/8 in*	5/32 in*	4 23/32 in*	1 5/32 in*	1 5/32 in*	Box
808000SN	1 1/2 in*	Satin Nickel	Stainless Steel	30 minutes	132 lb*			1 5/32 in*	4 1/8 in*	1/8 in*	UL / UL10C / ULC	180°	3 1/8 in*	11/16 in*	4 23/32 in*	1/8 in*	5/32 in*	4 23/32 in*	1 5/32 in*	1 5/32 in*	Box
802000SC	1 9/16 in*	Satin Chrome	Zinc Alloy (Zamak)			132 lb*	Self-Closing Hinge	2 17/32 in*	5 1/2 in*		Not Certified	180°	2 15/16 in*	19/32 in*	6 5/16 in*			6 5/16 in*	2 17/32 in*	2 17/32 in*	Per unit
807080SC	1 9/16 in*	Satin Chrome	Zinc Alloy (Zamak)		176 lb*	220 lb*					UL / UL10C / ULC / CE										Per unit
807120SC	1 9/16 in*	Satin Chrome	Zinc Alloy (Zamak)	30 minutes	265 lb*	309 lb*					UL / UL10C / ULC / CE		1 1/4 in*		7 7/8 in*				1 5/16 in*		Per unit
802000SN	1 9/16 in*	Satin Nickel	Zinc Alloy (Zamak)			132 lb*	Self-Closing Hinge	2 17/32 in*	5 1/2 in*		Not Certified	180°	2 15/16 in*	19/32 in*	6 5/16 in*	1/8 in*	5/32 in*	6 5/16 in*	2 17/32 in*	2 17/32 in*	Per unit
807080SN	1 9/16 in*	Satin Nickel	Zinc Alloy (Zamak)		176 lb*	220 lb*					UL / UL10C / ULC / CE		1 3/16 in*		6 5/16 in*				1 7/32 in*		Per unit
807200SN	1 9/16 in*	Satin Nickel	Zinc Alloy (Zamak)		441 lb*						Not Certified		1 1/4 in*		9 1/16 in*				1 5/16 in*		Per unit
807120SN	1 9/16 in*	Satin Nickel	Zinc Alloy (Zamak)	30 minutes	265 lb*	309 lb*					UL / UL10C / ULC / CE		1 1/4 in*		7 7/8 in*				1 5/16 in*		Per unit
807120ST	1 9/16 in*	Steel	Zinc Alloy (Zamak)	30 minutes	265 lb*	309 lb*					UL / UL10C / ULC / CE		1 1/4 in*		7 7/8 in*				1 5/16 in*		Per unit

TECHNICAL SPECIFICATIONS

Type of Hinge	Wood Door Only
Brand	Krona Koblenz
Screw/Nail	Included
Fixing Type	Screw-On
Mounting Type	Mortise
Handedness	Reversible
Hinge Opening Angle	+180°

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

IMPORTANT INFORMATION

2 Year Warranty

PRODUCT PHOTOS

