



Magic 2 Legno Sliding Door System

Overall Length

43 1/4 in*

70 7/8 in*

Door Width

33 1/2 to 43 1/4 in*

35 3/8 to 70 7/8 in*

DESCRIPTION

Completely concealed hardware and track

The Magic 2 Legno is a bottom-running sliding system for wood doors weighing up to 176 lb (80 kg) each.

- Bottom running with a concealed upper guide in kit format
- Includes dampener to stop the door in both directions
- For door widths up to 43 in (1.1 m) and 70 in (1.8 m)
- Can be cut and fitted for a wide variety of door widths and thicknesses
- Non-marking bottom rollers do not require a track
- For hard smooth floor surfaces

The Magic 2 Legno is ideal for residential interior doors, the hospitality sector, and commercial offices.

Unique hardware and concealed track create the illusion of a floating door.

IMPORTANT: Use metric dimensions for greater accuracy during installation. Cut a groove at the bottom of the door as per instruction 24 x 21 mm (1 x 7/8 in) for the bottom wheels and 12 x 21 mm (1/2 x 7/8 in) for the bottom guide rail. When calculating door dimensions read instructions carefully, and consider 170 mm (6 3/4 in) door overlap and an additional 50 mm (2 in) to reduce sight lines.

ADVANTAGES AND BENEFITS

- Its unique hardware and concealed track create the illusion that the door is floating -
- The slide system is built into the door, making it completely invisible whether the door is closed or open -
- Smooth sliding system -
- The mounting plate is designed to be wall-mounted

AVAILABLE PRODUCTS

Product #	Overall Length	Door Width
89M21100	43 1/4 in*	33 1/2 to 43 1/4 in*
89M21800	70 7/8 in*	35 3/8 to 70 7/8 in*

TECHNICAL SPECIFICATIONS

Door Material	Wood
Detailed Door Movement	Single sliding
Track Mounting	Floor Mount
Load Capacity	88.2 to 176 lb*
Door Position	In Front of Wall
Door Thickness	1 3/8 to 2 5/32 in*
Roller Position	Upper
Application	Sliding Wall, Standard Access Door, Barn Door
Track type	Running
Soft-Closing	Yes
Product type	Complete Set
Groove Needed for Guiding System	Yes
Door Installation	Bottom Running
Number of Doors	1
Door Height	70 7/8 to 104 in*

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

IMPORTANT INFORMATION

- Pictures provided for visual reference only: actual product may vary. - All required hardware should be ordered and obtained prior to initiating fabrication or installation work. Please verify that the parts and quantities listed in your order are correct before proceeding to checkout. - Always use instructions provided by the manufacturer, as included with the product. Manufacturer reserves the right to amend, modify, or otherwise supplement any previously issued product and/or technical information, as deemed required from time to time, without prior notice. - The documentation, drawings, and instructions on this page apply to the system described on this page only. Richelieu expressly declines all responsibility for any design or construction that combines this system with systems from this same manufacturer or systems from other manufacturers. - Installation of the product shall be executed by qualified individuals only, always ensuring that each product is securely installed using proper fixation methods, as appropriate for each applicable substratum. We trust that anyone installing these products has the required skills, knowledge, and experience. Richelieu expressly disclaims any liabilities for results obtained through improper use or installation. - Always remove debris/dust/residues (sawdust and/or aluminum) from all tracks and guide channels using a dry cloth during installation and before operating the system. - Never spray lubricant.

DISCLAIMER

By accessing or referring to this document, or by using any of Richelieu's websites, you accept all applicable terms as they apply from time to time. This legal disclaimer is in no way limited or altered by any other terms or conditions. Richelieu may change said terms at its discretion and without prior notice. A version of the most current terms will always be available on Richelieu's website. The preceding information and technical documentation, information, or recommendations issued by Richelieu verbally or in writing is believed to be accurate and is given in good faith, but no representation of warranty as to its completeness or accuracy is made. Suggestions for use or application are only opinions. Users are responsible for determining the suitability of these products for their own particular purpose. No representation of warranty, expressed or implied, is made with respect to information or products including, without limitation, warranties or merchantability, fitness for particular purpose, non-infringement of any third party patent or other intellectual property rights including, without limit, copyright, trademark, and designs. Any trademarks identified herein are trademarks of the Richelieu group of companies. Richelieu assumes no risk and shall not be subject to any liability for damages or loss resulting from the specific use or application made of the product. Richelieu's liability for any claim, whether based on breach of contract, negligence, or infringement of any rights of any party relating to the product shall not exceed the price paid for said products. In no event shall Richelieu be liable for any special, incidental, or consequential damages (including loss of use, loss of profit, and claims of third parties) however caused, whether by the negligence of Richelieu or otherwise. Products returned for warranty purposes shall be subject to Richelieu's then applicable Return Policy.

PRODUCT PHOTOS

