



## K-PAD LED Panel Light - 5 W, 24 V

### Control System



### Operation



### Finish



### Light Color

Neutral White

Warm White

### Kelvin Color Temperature (K)

3100 K

4000 K

### Features

On/off  
Touchless  
Dimmer

Without  
Switch

## DESCRIPTION

### High power 5 W

- Integrates a special EDGE LED cluster which guarantees a wide projection beam and allows uniform illumination on the working surface.
- Designed for quick surface mount installation with a thickness of only 5/16 in (8 mm).
- Built-in control function which turns all the lights on and off and dims the K-Pads without switch option.
- Can also use K-Pads without switch option on its own and choose from a wide variety of other dimming accessories.
- Perfect for under-cabinet lighting.

## ADVANTAGES AND BENEFITS

- From Italy exclusive to Richelieu - Available in three versions - An LED panel only 5/16 in (8 mm) thick designed for quick surface installation - Also configured with a dimming switch to regulate the intensity of light - One K-Pad master can control up to five K-Pads without switch

## AVAILABLE PRODUCTS

Product #	Control System	Operation	Finish	Light Color	Kelvin Color Temperature (K)	Features
<b>128122900</b>			Black	Warm White	3100 K	Without Switch
<b>128124170</b>			Stainless Steel	Neutral White	4000 K	Without Switch
<b>128122030</b>			White	Warm White	3100 K	Without Switch
<b>127122900</b>	Touch	Touch	Black	Warm White	3100 K	On/off Touchless Dimmer
<b>127124170</b>	Touch	Touch	Stainless Steel	Neutral White	4000 K	On/off Touchless Dimmer
<b>127124030</b>	Touch	Touch	White	Neutral White	4000 K	On/off Touchless Dimmer
<b>127122030</b>	Touch	Touch	White	Warm White	3100 K	On/off Touchless Dimmer

## TECHNICAL SPECIFICATIONS

Location	Inside Cabinet, Under Cabinet, Closet, Countertop
Application	Kitchen, Bedroom
Mounting	Surface
Luminaire	Fixed Spots
Compatibility	Micro 24
Lighting	Task
Standards and Certifications	ETL, ULC, cULus
Style	Contemporary
CRI (Color Rendering Index)	80
Luminous Efficiency	55 lm/W
Length	7 3/32 in*
Height	5/16 in*
Width	2.984375 in
IP	IP20
Lighting Type	LED
Tension (V)	24 V
Watts	5 W
Group	LED Group A, LED 24 V dc Exclusive
Connection Type	Micro 24
Luminous Flux	275 Lumen

### Disclaimer

Measures shown with an asterisk (\*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

## INCLUDED PRODUCT(S)

- K-Pad LED panel light - 78 3/4 in (2 m) power cable with a Micro24 connector

## APPLICATION

- Kitchen counter. - Add K-Pad to your interior cabinet design to complete the look.

## IMPORTANT INFORMATION

- New addition to the K-Pad 24 V dc line of products from Italy exclusive to Richelieu. - Available in three versions: - K-Pad Touch master with dimmer switch (built-in touch LED dimmer) - K-Pad without dimmer switch (without integrated IR switch) - K-Pad (IR) with infrared proximity sensor - One K-Pad master can control up to five K-Pads without switch - SMD EDGE LED technology - Luminous efficiency: 55 in

## DISCLAIMER

- Product information subject to change without notice - Use prescribed power supply - Indoor use only

## PRODUCT PHOTOS

