



HAWA JUNIOR B Series Sliding Door System

Detailed Door Movement

Biparting

Bypassing

Single sliding

Load Capacity

44.1 to 88.2 lb*

90.4 to 176 lb*

179 to 220 lb*

223 to 265 lb*

267 to 353 lb*

355 to 551 lb*

Door Thickness

1 3/16 to 1 25/32 in*

1 3/16 to 2 3/8 in*

1 3/8 to 1 31/32 in*


1 1/2 to 2 1/4 in*

1 9/16 to 3 5/32 in*

Application



Closet and Walk-In Closet



Sliding Wall



Standard Access Door



Closet and Walk-In Closet / Standard Access Door



Sliding Wall / Standard Access Door

Overall Length

63 in*

70 7/8 in*

78 3/4 in*

98 3/8 in*

9 ft 10 in*

11 ft 5 in*

13 ft 1 in*

16 ft 4 in*

19 ft 8 in*

Soft-Closing

No

Yes

Soft-Close Type

1 soft close

4 soft close

None

Two Soft-close

Number of Doors

1

2

3

Door Height

59 to 118 in*

70 7/8 to 157 in*

78 3/4 to 157 in*

Door Width

21 5/8 to 41 3/8 in*

23 5/8 to 48 in*

25 5/8 to 39 3/8 in*

25 5/8 to 49 1/4 in*

27 1/8 to 30 1/2 in*

27 1/8 to 32 1/2 in*

27 1/8 to 36 3/8 in*

27 1/8 to 40 3/8 in*

29 1/2 to 49 1/4 in*

31 1/2 to 39 3/8 in*

31 1/2 to 59 in*

32 5/8 to 39 3/8 in*

36 to 49 1/4 in*

36 to 59 in*

36 to 78 3/4 in*

36 to 98 3/8 in*

39 3/8 to 59 in*

39 3/8 to 78 3/4 in*

40 1/2 to 50 1/4 in*

40 1/2 to 59 in*

45 1/4 to 59 in*

45 1/4 to 60 in*

DESCRIPTION

Mortise mount suspension plate for low headroom applications

The HAWA JUNIOR B Series sliding wood door systems for doors weighing 88 lb to 550 lb (40 kg to 250 kg) per door.

- Low profile rebate/mortise mount suspension plate for the top of the door
- Minimal gap between the top of the door and upper track, does not require a fascia
- Integrated track stopper with adjustable retaining device to resist door bounce back
- Versatile track options in various lengths for single sliding, biparting, and bypassing applications
- Smooth and quiet premium performance and long-lasting trolleys
- Available SoftMove soft/self-closing mechanism sold separately for doors weighing from 88 lb to 264 lb (40 kg to 120 kg) per door

The HAWA JUNIOR B Series is an ideal solution for premium commercial and residential projects, room dividers, pocket doors, wall partitions, and low headroom applications.

ADVANTAGES AND BENEFITS

- Low profile rebate/mortise mount suspension plate
- Minimal installation height
- Quiet action
- Track stopper with adjustable retaining device

AVAILABLE PRODUCTS

Product #	Detailed Door Movement	Load Capacity	Door Thickness	Application	Overall Length	Soft-Closing	Soft-Close Type	Number of Doors	Door Height	Door Width
WEBKIT1224363	Biparting	44.1 to 88.2 lb*	1 3/16 to 1 25/32 in*	Standard Access Door	13 ft 1 in*	Yes	None	2	59 to 118 in*	32 5/8 to 39 3/8 in*
WEBKIT1236457	Biparting	90.4 to 176 lb*	1 3/8 to 1 31/32 in*	Standard Access Door	9 ft 10 in*	No	None	2	70 7/8 to 157 in*	27 1/8 to 30 1/2 in*
WEBKIT1236458	Biparting	90.4 to 176 lb*	1 3/8 to 1 31/32 in*	Standard Access Door	13 ft 1 in*	No	None	2	70 7/8 to 157 in*	27 1/8 to 40 3/8 in*

Product #	Detailed Door Movement	Load Capacity	Door Thickness	Application	Overall Length	Soft-Closing	Soft-Close Type	Number of Doors	Door Height	Door Width
WEBKIT1236459	Biparting	90.4 to 176 lb*	1 3/8 to 1 31/32 in*	Standard Access Door	19 ft 8 in*	Yes	4 soft close	2	70 7/8 to 157 in*	40 1/2 to 59 in*
WEBKIT1243927	Biparting	179 to 220 lb*	1 3/16 to 2 3/8 in*	Standard Access Door	13 ft 1 in*	Yes	4 soft close	2	78 3/4 to 157 in*	31 1/2 to 39 3/8 in*
WEBKIT1243928	Biparting	179 to 220 lb*	1 3/16 to 2 3/8 in*	Standard Access Door	19 ft 8 in*	Yes	4 soft close	2	78 3/4 to 157 in*	31 1/2 to 59 in*
WEBKIT1010601	Biparting	223 to 265 lb*	1 1/2 to 2 1/4 in*	Sliding Wall / Standard Access Door	19 ft 8 in*	Yes	4 soft close	2	70 7/8 to 157 in*	45 1/4 to 59 in*
WEBKIT1236460	Biparting	223 to 265 lb*	1 1/2 to 2 1/4 in*	Sliding Wall / Standard Access Door	19 ft 8 in*	Yes	4 soft close	2	70 7/8 to 157 in*	45 1/4 to 60 in*
WEBKIT1010614	Biparting	267 to 353 lb*	1 1/2 to 2 1/4 in*	Sliding Wall / Standard Access Door	16 ft 4 in*	No	None	2	78 3/4 to 157 in*	36 to 49 1/4 in*
WEBKIT1236462	Biparting	267 to 353 lb*	1 1/2 to 2 1/4 in*	Sliding Wall / Standard Access Door	19 ft 8 in*	No	None	2	78 3/4 to 157 in*	36 to 59 in*
WEBKIT1010616	Biparting	355 to 551 lb*	1 9/16 to 3 5/32 in*	Sliding Wall	19 ft 8 in*	No	None	2	78 3/4 to 157 in*	39 3/8 to 59 in*
WEBKIT1236468	Bypassing	44.1 to 88.2 lb*	1 3/16 to 1 25/32 in*	Closet and Walk-In Closet	78 3/4 in*	No	None	2	59 to 118 in*	21 5/8 to 41 3/8 in*
WEBKIT1243846	Bypassing	44.1 to 88.2 lb*	1 3/16 to 1 25/32 in*	Closet and Walk-In Closet	11 ft 5 in*	No	None	3	59 to 118 in*	23 5/8 to 48 in*
WEBKIT1236463	Bypassing	267 to 353 lb*	1 1/2 to 2 1/4 in*	Sliding Wall	16 ft 4 in*	No	None	2	78 3/4 to 157 in*	36 to 98 3/8 in*
WEBKIT1216571	Single sliding	44.1 to 88.2 lb*	1 3/16 to 1 25/32 in*	Closet and Walk-In Closet / Standard Access Door	78 3/4 in*	Yes	Two Soft-close	1	59 to 118 in*	32 5/8 to 39 3/8 in*
WEBKIT1214995	Single sliding	90.4 to 176 lb*	1 3/8 to 1 31/32 in*	Standard Access Door	63 in*	No	None	1	70 7/8 to 157 in*	27 1/8 to 32 1/2 in*
WEBKIT1214996	Single sliding	90.4 to 176 lb*	1 3/8 to 1 31/32 in*	Standard Access Door	70 7/8 in*	No	None	1	70 7/8 to 157 in*	27 1/8 to 36 3/8 in*
WEBKIT1216578	Single sliding	90.4 to 176 lb*	1 3/8 to 1 31/32 in*	Standard Access Door	78 3/4 in*	No	None	1	70 7/8 to 157 in*	27 1/8 to 40 3/8 in*
WEBKIT1236456	Single sliding	90.4 to 176 lb*	1 3/8 to 1 31/32 in*	Standard Access Door	98 3/8 in*	Yes	Two Soft-close	1	70 7/8 to 157 in*	40 1/2 to 50 1/4 in*
WEBKIT1243924	Single sliding	179 to 220 lb*	1 3/16 to 2 3/8 in*	Standard Access Door	78 3/4 in*	No	None	1	78 3/4 to 157 in*	25 5/8 to 39 3/8 in*

Product #	Detailed Door Movement	Load Capacity	Door Thickness	Application	Overall Length	Soft-Closing	Soft-Close Type	Number of Doors	Door Height	Door Width
WEBKIT1243925	Single sliding	179 to 220 lb*	1 3/16 to 2 3/8 in*	Standard Access Door	98 3/8 in*	Yes	1 soft close	1	78 3/4 to 157 in*	25 5/8 to 49 1/4 in*
WEBKIT1243926	Single sliding	179 to 220 lb*	1 3/16 to 2 3/8 in*	Standard Access Door	9 ft 10 in*	Yes	Two Soft-close	1	78 3/4 to 157 in*	31 1/2 to 59 in*
WEBKIT1010598	Single sliding	223 to 265 lb*	1 1/2 to 2 1/4 in*	Standard Access Door	98 3/8 in*	No	None	1	78 3/4 to 157 in*	29 1/2 to 49 1/4 in*
WEBKIT1010599	Single sliding	223 to 265 lb*	1 1/2 to 2 1/4 in*	Sliding Wall / Standard Access Door	9 ft 10 in*	Yes	Two Soft-close	1	78 3/4 to 157 in*	45 1/4 to 60 in*
WEBKIT1010613	Single sliding	267 to 353 lb*	1 1/2 to 2 1/4 in*	Sliding Wall / Standard Access Door	9 ft 10 in*	No	None	1	78 3/4 to 157 in*	36 to 59 in*
WEBKIT1236461	Single sliding	267 to 353 lb*	1 1/2 to 2 1/4 in*	Sliding Wall / Standard Access Door	13 ft 1 in*	No	None	1	78 3/4 to 157 in*	36 to 78 3/4 in*
WEBKIT1010615	Single sliding	355 to 551 lb*	1 9/16 to 3 5/32 in*	Sliding Wall / Standard Access Door	13 ft 1 in*	No	None	1	78 3/4 to 157 in*	39 3/8 to 78 3/4 in*

TECHNICAL SPECIFICATIONS

Door Material	Wood
Door Movement	Straight Sliding
Track Mounting	Ceiling Mount
Door Position	Inside Frame
Brand	Hawa
Finish	Satin Aluminum
Adjustable	Yes
Door Installation	Top Hung

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

IMPORTANT INFORMATION

- Pictures provided for visual reference only: actual product may vary. - All required hardware should be ordered and obtained prior to initiating fabrication or installation work. Please verify that the parts and quantities listed in your order are correct before proceeding to checkout. - Always use instructions provided by the manufacturer, as included with the product. Manufacturer reserves the right to amend, modify, or otherwise supplement any previously issued product and/or technical information, as deemed required from time to time, without prior notice. - The documentation, drawings, and instructions on this page apply to the system described on this page only. Richelieu expressly declines all responsibility for any design or construction that combines this system with systems from this same manufacturer or systems from other manufacturers. - Installation of the product shall be executed by qualified individuals only, always ensuring that each product is securely installed using proper fixation methods, as appropriate for each applicable substratum. We trust that anyone installing these products has the required skills, knowledge, and experience. Richelieu expressly disclaims any liabilities for results obtained through improper use or installation. - Always remove debris/dust/residues (sawdust and/or aluminum) from all tracks and guide channels using a dry cloth during installation and before operating the system. - Never spray lubricant.

DISCLAIMER

By accessing or referring to this document, or by using any of Richelieu's websites, you accept all applicable terms as they apply from time to time. This legal disclaimer is in no way limited or altered by any other terms or conditions. Richelieu may change said terms at its discretion and without prior notice. A version of the most current terms will always be available on Richelieu's website. The preceding information and technical documentation, information, or recommendations issued by Richelieu verbally or in writing is believed to be accurate and is given in good faith, but no representation of warranty as to its completeness or accuracy is made. Suggestions for use or application are only opinions. Users are responsible for determining the suitability of these products for their own particular purpose. No representation of warranty, expressed or implied, is made with respect to information or products including, without limitation, warranties or merchantability, fitness for particular purpose, non-infringement of any third party patent or other intellectual property rights including, without limit, copyright, trademark, and designs. Any trademarks identified herein are trademarks of the Richelieu group of companies. Richelieu assumes no risk and shall not be subject to any liability for damages or loss resulting from the specific use or application made of the product. Richelieu's liability for any claim, whether based on breach of contract, negligence, or infringement of any rights of any party relating to the product shall not exceed the price paid for said products. In no event shall Richelieu be liable for any special, incidental, or consequential damages (including loss of use, loss of profit, and claims of third parties) however caused, whether by the negligence of Richelieu or otherwise. Products returned for warranty purposes shall be subject to Richelieu's then applicable Return Policy.

PRODUCT PHOTOS

