



## HAWA-Junior Z Series Straight Sliding Door System

### Track Mounting

Ceiling Mount	Wall Mount
---------------	------------

### Load Capacity

44.1 to 88.2 lb*	90.4 to 176 lb*	179 to 220 lb*
------------------	-----------------	----------------

### Door Thickness

1 3/16 to 1 3/8 in*	1 3/16 to 1 25/32 in*	1 3/16 to 3 5/32 in*
---------------------	-----------------------	----------------------

### Overall Length

63 in*	70 7/8 in*	78 3/4 in*	98 3/8 in*	9 ft 10 in*
13 ft 1 in*	19 ft 8 in*			

### Soft-Closing

No	Yes
----	-----

### Soft-Close Type

1 soft close	4 soft close	None	Two Soft-close
--------------	--------------	------	----------------

### Number of Doors

1	2
---	---

### Door Width

21 5/8 to 33 1/2 in*	21 5/8 to 37 3/8 in*	21 5/8 to 41 3/8 in*	25 5/8 to 31 1/2 in*	25 5/8 to 39 3/8 in*
25 5/8 to 59 in*	31 1/2 to 39 3/8 in*	31 1/2 to 59 in*	32 5/8 to 41 3/8 in*	40 1/2 to 41 3/8 in*
40 1/2 to 49 1/4 in*	40 1/2 to 59 in*			

## DESCRIPTION

### Top-hung surface-mount two-way suspension plate

The HAWA-Junior Z Series, featuring the HAWA-Junior 40/Z, Junior 80/Z, and Junior

100/Z is a standard straight-sliding system for wood doors weighing up to 100 kg.

#### Features:

- Surface top-mount two-way suspension plate
- Integrated track stopper with adjustable retaining device to resist door bounce back
- SoftMove closing system (sold separately)
- Versatile track options for single sliding, bi parting, and bypassing applications
- Select from the following tracks:
  - a) Basic anodized track
  - b) Ceiling mount track for clip-on fascia
  - c) Wall mount track for clip-on fascia
- Smooth and quiet premium performance trolleys
- Flexible door installation

The HAWA-Junior Z Series is an ideal solution for commercial and premium residential projects. For use with doors between rooms, premium closets, and pocket doors.

**IMPORTANT:** Use metric dimensions for greater accuracy during installation. Cut a groove 12 mm x 20 mm at the bottom of the door for bottom guide.

## ADVANTAGES AND BENEFITS

- Two-way suspension plate for flexible door mounting
- Premium commercial grade hardware
- Performance certificate

## AVAILABLE PRODUCTS

Product #	Track Mounting	Load Capacity	Door Thickness	Overall Length	Soft-Closing	Soft-Close Type	Number of Doors	Door Width
<b>WEBKIT1216572</b>	Ceiling Mount	44.1 to 88.2 lb*	1 3/16 to 3 5/32 in*	78 3/4 in*	Yes	Two Soft-close	1	32 5/8 to 41 3/8 in*
<b>WEBKIT1216573</b>	Ceiling Mount	44.1 to 88.2 lb*	1 3/16 to 3 5/32 in*	13 ft 1 in*	Yes	4 soft close	2	32 5/8 to 41 3/8 in*
<b>WEBKIT1243303</b>	Ceiling Mount	90.4 to 176 lb*	1 3/16 to 1 3/8 in*	78 3/4 in*	Yes	Two Soft-close	1	40 1/2 to 41 3/8 in*
<b>WEBKIT1243304</b>	Ceiling Mount	90.4 to 176 lb*	1 3/16 to 1 3/8 in*	9 ft 10 in*	Yes	Two Soft-close	1	40 1/2 to 59 in*
<b>WEBKIT1243299</b>	Ceiling Mount	90.4 to 176 lb*	1 3/16 to 1 25/32 in*	63 in*	No	None	1	21 5/8 to 33 1/2 in*
<b>WEBKIT1243300</b>	Ceiling Mount	90.4 to 176 lb*	1 3/16 to 1 25/32 in*	70 7/8 in*	No	None	1	21 5/8 to 37 3/8 in*
<b>WEBKIT1216577</b>	Ceiling Mount	90.4 to 176 lb*	1 3/16 to 3 5/32 in*	78 3/4 in*	Yes	Two Soft-close	1	40 1/2 to 41 3/8 in*
<b>WEBKIT1234772</b>	Ceiling Mount	90.4 to 176 lb*	1 3/16 to 3 5/32 in*	98 3/8 in*	Yes	Two Soft-close	1	40 1/2 to 49 1/4 in*
<b>WEBKIT1234774</b>	Ceiling Mount	90.4 to 176 lb*	1 3/16 to 3 5/32 in*	9 ft 10 in*	No	None	2	21 5/8 to 33 1/2 in*
<b>WEBKIT1234773</b>	Ceiling Mount	90.4 to 176 lb*	1 3/16 to 3 5/32 in*	9 ft 10 in*	Yes	Two Soft-close	1	40 1/2 to 59 in*
<b>WEBKIT1234775</b>	Ceiling Mount	90.4 to 176 lb*	1 3/16 to 3 5/32 in*	13 ft 1 in*	Yes	4 soft close	2	40 1/2 to 41 3/8 in*
<b>WEBKIT1234776</b>	Ceiling Mount	90.4 to 176 lb*	1 3/16 to 3 5/32 in*	19 ft 8 in*	Yes	4 soft close	2	40 1/2 to 59 in*
<b>WEBKIT1243915</b>	Ceiling Mount	179 to 220 lb*	1 3/16 to 1 3/8 in*	78 3/4 in*	No	None	1	25 5/8 to 39 3/8 in*
<b>WEBKIT1243916</b>	Ceiling Mount	179 to 220 lb*	1 3/16 to 1 3/8 in*	78 3/4 in*	Yes	1 soft close	1	25 5/8 to 39 3/8 in*
<b>WEBKIT1243917</b>	Ceiling Mount	179 to 220 lb*	1 3/16 to 1 3/8 in*	78 3/4 in*	Yes	Two Soft-close	1	31 1/2 to 39 3/8 in*

Product #	Track Mounting	Load Capacity	Door Thickness	Overall Length	Soft-Closing	Soft-Close Type	Number of Doors	Door Width
<b>WEBKIT1243918</b>	Ceiling Mount	179 to 220 lb*	1 3/16 to 1 3/8 in*	9 ft 10 in*	No	None	2	25 5/8 to 31 1/2 in*
<b>WEBKIT1243919</b>	Ceiling Mount	179 to 220 lb*	1 3/16 to 1 3/8 in*	9 ft 10 in*	Yes	Two Soft-close	1	31 1/2 to 59 in*
<b>WEBKIT1243298</b>	Wall Mount	90.4 to 176 lb*	1 3/16 to 1 3/8 in*	78 3/4 in*	No	None	1	21 5/8 to 41 3/8 in*
<b>WEBKIT1243301</b>	Wall Mount	90.4 to 176 lb*	1 3/16 to 1 3/8 in*	9 ft 10 in*	Yes	Two Soft-close	1	40 1/2 to 59 in*
<b>WEBKIT1243297</b>	Wall Mount	90.4 to 176 lb*	1 3/16 to 1 25/32 in*	78 3/4 in*	No	None	1	21 5/8 to 41 3/8 in*
<b>WEBKIT1243302</b>	Wall Mount	90.4 to 176 lb*	1 3/16 to 1 25/32 in*	9 ft 10 in*	Yes	Two Soft-close	1	40 1/2 to 59 in*
<b>WEBKIT1243920</b>	Wall Mount	179 to 220 lb*	1 3/16 to 1 25/32 in*	78 3/4 in*	No	None	1	25 5/8 to 39 3/8 in*
<b>WEBKIT1243922</b>	Wall Mount	179 to 220 lb*	1 3/16 to 1 25/32 in*	78 3/4 in*	Yes	Two Soft-close	1	31 1/2 to 39 3/8 in*
<b>WEBKIT1243923</b>	Wall Mount	179 to 220 lb*	1 3/16 to 1 25/32 in*	9 ft 10 in*	No	None	1	25 5/8 to 59 in*
<b>WEBKIT1243921</b>	Wall Mount	179 to 220 lb*	1 3/16 to 1 25/32 in*	9 ft 10 in*	Yes	Two Soft-close	1	31 1/2 to 59 in*

## TECHNICAL SPECIFICATIONS

<b>Door Material</b>	Wood
<b>Door Movement</b>	Straight Sliding
<b>Detailed Door Movement</b>	Single sliding
<b>Roller Position</b>	Upper
<b>Application</b>	Closet and Walk-In Closet, Standard Access Door, Pocket Door
<b>Brand</b>	Hawa
<b>Manufacturing Material</b>	Aluminum
<b>Finish</b>	Anodized Aluminum
<b>Stopper</b>	Two
<b>Groove Needed for Guiding System</b>	Yes
<b>Door Installation</b>	Top Hung
<b>Door Height</b>	Max. 10 ft*
<b>Brand Model</b>	Hawa Junior

### Disclaimer

Measures shown with an asterisk (\*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

## IMPORTANT INFORMATION

**IMPORTANT:** - Use metric dimensions for greater accuracy during installation. - Cut a groove 15/32 in (12 mm) x 25/32 in (20 mm) at the bottom of the door for bottom guide. - Pictures provided for visual reference only: actual product may vary. - All required hardware should be ordered and obtained prior to initiating fabrication or installation work. Please verify that the parts and quantities listed in your order are correct before proceeding to checkout. - Always use instructions provided by the manufacturer, as included with the product. Manufacturer reserves the right to amend, modify, or otherwise supplement any previously issued product and/or technical information, as deemed required from time to time, without prior notice. - The documentation, drawings, and instructions on this page apply to the system described on this page only. Richelieu expressly declines all responsibility for any design or construction that combines this system with systems from this same manufacturer or systems from other manufacturers. - Installation of the product shall be executed by qualified individuals only, always ensuring that each product is securely installed using proper fixation methods, as appropriate for each applicable substratum. We trust that anyone installing these products has the required skills, knowledge, and experience. Richelieu expressly disclaims any liabilities for results obtained through improper use or installation. - Always remove debris/dust/residues (sawdust and/or aluminum) from all tracks and guide channels using a dry cloth during installation and before operating the system. - Never spray lubricant.

## DISCLAIMER

By accessing or referring to this document, or by using any of Richelieu's websites, you accept all applicable terms as they apply from time to time. This legal disclaimer is in no way limited or altered by any other terms or conditions. Richelieu may change said terms at its discretion and without prior notice. A version of the most current terms will always be available on Richelieu's website. The preceding information and technical documentation, information, or recommendations issued by Richelieu verbally or in writing is believed to be accurate and is given in good faith, but no representation of warranty as to its completeness or accuracy is made. Suggestions for use or application are only opinions. Users are responsible for determining the suitability of these products for their own particular purpose. No representation of warranty, expressed or implied, is made with respect to information or products including, without limitation, warranties or merchantability, fitness for particular purpose, non-infringement of any third party patent or other intellectual property rights including, without limit, copyright, trademark, and designs. Any trademarks identified herein are trademarks of the Richelieu group of companies. Richelieu assumes no risk and shall not be subject to any liability for damages or loss resulting from the specific use or application made of the product. Richelieu's liability for any claim, whether based on breach of contract, negligence, or infringement of any rights of any party relating to the product shall not exceed the price paid for said products. In no event shall Richelieu be liable for any special, incidental, or consequential damages (including loss of use, loss of profit, and claims of third parties) however caused, whether by the negligence of Richelieu or otherwise. Products returned for warranty purposes shall be subject to Richelieu's then applicable Return Policy.

## PRODUCT PHOTOS

