



Pacta Drop-Down Door System

Motion Technology

Soft-Opening

Push-to-Open
/ Soft-Opening

Load Capacity

4.41 to 8.82
lb*

6.61 to 13.2
lb*

8.82 to 19.8
lb*

DESCRIPTION

A compact hinge for drop-down doors that operates without the need for additional stays or cables.

- This opening system offers a decelerated opening action and the fall of the door is gradual and controlled.
- In the fully-open position, the door and bottom panel are aligned, creating a uniform and flat surface.
- Also available with push self-opening system and comes in a variety of finishes.

Comprised of two separate types of hinges:

- The main hinge controls the opening and closing action.
- The second is an optional flap hinge, to insure the perfect alignment of the door with the bottom panel.

AVAILABLE PRODUCTS

Product #	Motion Technology	Load Capacity
FRBKFEXWSN9	Soft-Opening	4.41 to 8.82 lb*
FRBKFEXISN9	Soft-Opening	6.61 to 13.2 lb*
FRBKFEXSSN9	Soft-Opening	8.82 to 19.8 lb*
FRBKFEPWSN9	Push-to-Open / Soft-Opening	4.41 to 8.82 lb*
FRBKFEPISN9	Push-to-Open / Soft-Opening	6.61 to 13.2 lb*
FRBKFEPSSN9	Push-to-Open / Soft-Opening	8.82 to 19.8 lb*

TECHNICAL SPECIFICATIONS

Brand	Salice
System Type	Pacta
Type of Opening	Drop-Down Opening
Door Type	Wood Door
Door Height	11 to 15 3/4 in*
Opening Types	Drop-Down Opening
Material	Steel
Hinge Opening Angle	+90°

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

APPLICATION

Kitchen cabinets, bathroom cabinets and living rooms, as well as in commercial applications. - The ideal solution for residential and commercial furniture where an added work surface is desired. - Due to an ample load rating, Pacta can create a functional writing surface, a serving area or an extension for a variety of purposes. - For wood doors only.

IMPORTANT INFORMATION

- The #7 x 5/8" (15.85 mm) coarse thread flat head wood screws may be substituted the Euro screws included in the kit. - Pacta is capable of supporting considerable weight. If the open door is to be used as a work surface or to hold an appliance, please consult the technical drawing for the actual load rating based on the door size. - The flap hinge is required for doors wider than 30" (762 mm). Screw the hinge into the 1-3/8" (35 mm) holes on the unit and cover with screw cap. - The covers are not included and must be ordered separately. - The center hinge is required for doors 30" or wider. The center hinge is fully cam adjustable.

INCLUDED PRODUCT(S)

Box kit includes: - 2 Pacta hinges - 2 mounting plates - 2 Smove and screws

PRODUCT PHOTOS



