



# X-SIGN 4F - LED Light with Touch Switch, 10 W, 24 V

**Control System** 



#### Light Color

Neutral White Warm White

# Kelvin Color Temperature (K)

2900 K 3900 K

#### **Luminous Efficiency**

40 lm/W 48 lm/W

#### Luminous Flux

400 Lumen 480 Lumen

#### Features



# DESCRIPTION

#### LED light for wall installation. A unique 10 W high-power design.

- Integrates a LGP LED technology which guarantees a wide projection beam with a distinctive design and diffuser for perfect opalescence.

- Designed for quick surface-mount installation with a thickness of 3/8 in (10 mm).
- Has a uniform and diffused light projection which is devoid of the dot effect.

# **ADVANTAGES AND BENEFITS**

- One master X-Sign can control up to five X-Signs without a switch - Simple screw-on fitting - Bright and uniform light distribution - Offers high performance lighting, from full brightness to a comforting glow



# **AVAILABLE PRODUCTS**

Product #	Control System	Light Color	Kelvin Color Temperature (K)	Luminous Efficiency	Luminous Flux	Features
1283024124030		Neutral White	3900 K	48 lm/W	480 Lumen	Without Switch
1283024122030		Warm White	2900 K	40 lm/W	400 Lumen	Without Switch
1284024124030	Touch	Neutral White	3900 K	48 lm/W	480 Lumen	Touch Function
1284024122030	Touch	Warm White	2900 K	40 lm/W	400 Lumen	Touch Function

# **TECHNICAL SPECIFICATIONS**

Location	Wall Mounted
Application	Bedroom, Office, Commercial
Mounting	Surface
Luminaire	Fixed Spots
Compatibility	Micro 24
Operation	Touch
Lighting	Ambience, Accent
Finish	White
Standards and Certifications	cULus
Style	Contemporary, Eclectic
CRI (Color Rendering Index)	80
Length	4 1/16 in*
Height	13/32 in*
Width	7 1/16 in*
IP	IP20
Tension (V)	24 V
Watts	10 W
Group	LED Group A
Connection Type	Micro 24

#### Disclaimer

Measures shown with an asterisk (\*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, <u>click here</u>.

# **INCLUDED PRODUCT(S)**

- X-Sign 4F LED light - 78 3/4 in (2 m) power cable with a Micro24 connector



#### **IMPORTANT INFORMATION**

- Integrates a dimmable master electronic touch switch that allows switching on, switching off, and adjusting the light intensity of the individual luminaire and all the luminaires connected to it. - LED converter not included (to be ordered separately).

# APPLICATION

- Ideal on flat surfaces such as ceilings - Walls - Shelves

#### DISCLAIMER

- Product information subject to change without notice - Use prescribed power supply - Indoor use only - LED converter not included (to be ordered separately)

# **PRODUCT PHOTOS**









