



## FlexyLED LED Tape HE CR 24 V

### Light Color

Neutral White

Warm White

### Kelvin Color Temperature (K)

3000 K - 3400 K

4250 K - 4600 K

### Length

19 5/8 in\*

39 3/8 in\*

78 3/4 in\*

9 ft 10 in\*

### Watts

4.8 W

9.6 W

19.2 W

28.8 W

### Luminous Flux

1632 Lumen

1652 Lumen

2448 Lumen

2478 Lumen

408 Lumen

413 Lumen

816 Lumen

826 Lumen

## DESCRIPTION

### 9.6 W/m power, with IP44 rating

- Resin silicone-coated material that protects the LED strip from dust, moisture, and water splashes.
- An innovative quick-plug system designed for connecting modules of different lengths in a continuous row while maintaining the distance between the LED lights and ensuring a perfectly uniform light distribution.

## ADVANTAGES AND BENEFITS

- Flexible LED tape available in different lengths.
- Can be cut every 2 in (50 mm) or six LED lights.
- Quick connect system, no soldering of wires.
- The highly resistant double-sided adhesive provides fast installation without the use of any tools.
- The resin protects each LED strip against moderate mechanical shock and water splashes.
- Compatible dimmer switches available (see Suggested Products).

## AVAILABLE PRODUCTS

Product #	Light Color	Kelvin Color Temperature (K)	Length	Watts	Luminous Flux
<b>107024124020</b>	Neutral White	4250 K - 4600 K	19 5/8 in*	4.8 W	413 Lumen
<b>107024124040</b>	Neutral White	4250 K - 4600 K	39 3/8 in*	9.6 W	826 Lumen
<b>107024124079</b>	Neutral White	4250 K - 4600 K	78 3/4 in*	19.2 W	1652 Lumen
<b>107024124119</b>	Neutral White	4250 K - 4600 K	9 ft 10 in*	28.8 W	2478 Lumen
<b>107024122020</b>	Warm White	3000 K - 3400 K	19 5/8 in*	4.8 W	408 Lumen
<b>107024122040</b>	Warm White	3000 K - 3400 K	39 3/8 in*	9.6 W	816 Lumen
<b>1070241222079</b>	Warm White	3000 K - 3400 K	78 3/4 in*	19.2 W	1632 Lumen
<b>107024122119</b>	Warm White	3000 K - 3400 K	9 ft 10 in*	28.8 W	2448 Lumen

## TECHNICAL SPECIFICATIONS

<b>Location</b>	Under Cabinet, Countertop, Baseboard
<b>Application</b>	Kitchen, Bedroom, Commercial, Closet
<b>Mounting</b>	Recessed, Surface
<b>Luminaire</b>	Flexible Linear
<b>Compatibility</b>	Micro 24
<b>Lighting</b>	Accent, Task
<b>Standards and Certifications</b>	cULus
<b>CRI (Color Rendering Index)</b>	80
<b>Luminous Efficiency</b>	85 lm/W
<b>Height</b>	5/32 in*
<b>Width</b>	5/16 in*
<b>IP</b>	IP44
<b>Lighting Type</b>	LED
<b>Tension (V)</b>	24 V
<b>Group</b>	LED Group A
<b>Connection Type</b>	Micro 24

### Disclaimer

Measures shown with an asterisk (\*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

## IMPORTANT INFORMATION

- Tapes can be connected to one another to reach a maximum length of 235 in (5969 mm) - 120 LED/meter modules - Power cord required and sold separately (see Suggested Products) - Connecting cable sold separately (see Suggested Products)

---

## INCLUDED PRODUCT(S)

- FlexyLED CR tape light with 3MTM adhesive tape

## APPLICATION

- Kitchen - Toe kick - Bathrooms

## DISCLAIMER

- Product information subject to change without notice. - There is no replacement bulb available for this light due to its average lifespan of 50 000 hours. - Richelieu grants no warranty on LED lights if a power supply other than the one specifically prescribed for this product is used. - Do not exceed the maximum wattage by connecting more lights than prescribed; damage to the power supply may result. - Wattage calculation for power supplies should be using an 80% maximum yield. - Do not make the LED strip turn on itself. - Do not bend LED strip. - Power cord required and sold separately available in 79 in (2 m) length (please see Suggested Products). - 1 31/32 in (50 mm) connecting cable sold separately (please see Suggested Products). - Please contact the special orders desk for any special requests.

## PRODUCT PHOTOS

