



SEH4 - FlexyLED 12V Tape

Light Color

Neutral White

Warm White

Kelvin Color Temperature (K)

3100 K

4000 K

LED Strip Length

39 3/8 in*

78 3/4 in*

98 3/8 in*

9 ft 10 in*

Watts

12 W

22 W

27 W

30 W

Power Cable

Double

Single

DESCRIPTION

Silicone profile for recessed side emitting installations

- Silicone profile for recessed side-illuminated installations
- The FlexyLED SEH4 profile is designed for side lighting and can be installed directly in wood, in a groove 4 mm wide and 8 mm deep.
- This flexible 12 V linear LED strip has been developed using a new extrusion technology for the diffusion of silicone materials.
- Power 12 W/m, 120 LED/m.

ADVANTAGES AND BENEFITS

- Even lighting without dot effect - Fits in a recessed groove of only 4 mm in width - Pressure installation: no need for glue or adhesives, since the tape is made from a soft silicone and simply needs to be pressed into any type of groove - The flexibility of FlexyLED SE H4 makes it ideal for installing in any type of groove: linear, waves, rings, or any other shape - Can be cut every 25 mm

AVAILABLE PRODUCTS

Product #	Light Color	Kelvin Color Temperature (K)	LED Strip Length	Watts	Power Cable
128024124040	Neutral White	4000 K	39 3/8 in*	12 W	Single
128024124079	Neutral White	4000 K	78 3/4 in*	22 W	Single
128024124099	Neutral White	4000 K	98 3/8 in*	27 W	Single
128024124119	Neutral White	4000 K	9 ft 10 in*	30 W	Double
128024122040	Warm White	3100 K	39 3/8 in*	12 W	Double
128024122079	Warm White	3100 K	78 3/4 in*	22 W	Single
128024122099	Warm White	3100 K	98 3/8 in*	27 W	Double
128024122119	Warm White	3100 K	9 ft 10 in*	30 W	Double

TECHNICAL SPECIFICATIONS

Location	Under Cabinet, Countertop
Application	Kitchen, Living Room, Bedroom, Office, Commercial, Furniture, Closet
Mounting	Recessed
Luminaire	Flexible Linear
Compatibility	Micro 12
Lighting	Accent, Task
Standards and Certifications	cULus
CRI (Color Rendering Index)	80
Luminous Efficiency	70 lm/W
Power Cable Length	78 3/4 in*
Width	5/32 in*
Recessed Depth	13/32 in*
IP	IP44
Lighting Type	LED
Tension (V)	12 V
Group	LED Group A
Features	Dimmable

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

IMPORTANT INFORMATION

- Lighting efficiency: 70 lm/W - Once strip is cut, it cannot be reconnected - The FlexyLED SE H4 cannot be bent at right angles

INCLUDED PRODUCT(S)

- FlexyLED SE H4 pre-wired tape light - 78 3/4" (2 m) power cable with a Micro12 connector - Silicone cap

APPLICATION

- Countertops - Cabinets - Bookcases - Display cases - Decorative lighting - Wardrobes - Cupboards

DISCLAIMER

Product information is subject to change without prior notice. Richelieu grants no warranty on LED lights if a power supply other than the one specifically prescribed for this product is used. Do not exceed the maximum wattage by connecting more lights than prescribed as damage to the power supply may result.

PRODUCT PHOTOS



