



HE6 PW - FlexyLED 24 V

Light Color

Neutral White

Warm White

Kelvin Color Temperature (K)

3100 K

4200 K

LED Strip Length

19 5/8 in*

39 3/8 in*

78 3/4 in*

98 3/8 in*

9 ft 10 in*

Watts

4.8 W

9.6 W

19.2 W

24 W

28.8 W

DESCRIPTION

Flexible LED tape is Richelieu's narrowest LED tape; it's only 6 mm wide.

- The modules are designed with the reinforced power supply cable soldering pads which guarantee appropriate solidity.
- Comes with high-density, light-emitting diodes which eliminate the dotted effect.

ADVANTAGES AND BENEFITS

- Easily concealable and ultra narrow (6 mm wide) - Can be cut every 2 in (50 mm) or 6 LED lights - Can be slid into the APEX , LAB and MISS profiles. (see Suggested Products) - Provides a balanced power and appropriate heat dissipation so that it can be integrated into profiles without dissipaters.

AVAILABLE PRODUCTS

Product #	Light Color	Kelvin Color Temperature (K)	LED Strip Length	Watts
16612419	Neutral White	4200 K	19 5/8 in*	4.8 W
16612439	Neutral White	4200 K	39 3/8 in*	9.6 W
16612479	Neutral White	4200 K	78 3/4 in*	19.2 W
166124118	Neutral White	4200 K	9 ft 10 in*	28.8 W
16612219	Warm White	3100 K	19 5/8 in*	4.8 W
16612239	Warm White	3100 K	39 3/8 in*	9.6 W
16612279	Warm White	3100 K	78 3/4 in*	19.2 W
16612299	Warm White	3100 K	98 3/8 in*	24 W
166122118	Warm White	3100 K	9 ft 10 in*	28.8 W

TECHNICAL SPECIFICATIONS

Location	Inside Cabinet, Under Cabinet, Closet, Furniture
Application	Kitchen, Living Room, Furniture, Closet
Mounting	Recessed
Luminaire	Flexible Linear
Compatibility	Micro 24
Lighting	Ambience, Accent
Standards and Certifications	cULus
CRI (Color Rendering Index)	80
Luminous Efficiency	82 lm/W
Power Cable Length	78 3/4 in*
Width	1/4 in*
IP	IP20
Tension (V)	24 V
Group	LED Group A
Power Cable	Double
Connection Type	Micro 24
Features	Dimmable
Length of second power cable	78 3/4 in*

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

INCLUDED PRODUCT(S)

- FlexyLED HE6 PW pre-wired tape light - 78 3/4 in (2 m) power cable with a Micro24 connector

IMPORTANT INFORMATION

- 36.6 LED/ft, 120 LED/m - Rated power: 2.9 W/ft, 9.6 W/m - Equipped with a power supply cable and a connector.

DISCLAIMER

- Product information is subject to change without prior notice. - Richelieu grants no warranty on LED lights if a power supply other than the one specifically prescribed for this product is used. - Do not exceed the maximum wattage by connecting more lights than prescribed as damage to the power supply may result.

PRODUCT PHOTOS

