




## 1" (25 mm) Diameter Back-to-Back Ladder Handle

### Color/Finish



### Center to Center Drilling (Spacing)

12 in

24 in

### Door Type

Glass

Glass / Wood / Architectural

### Door Thickness

1 3/8 to 1 31/32 in\*

### Height

16 in

31 1/2 in

32 in

### Screw/Nail

Included / M6

Included / M8

## DESCRIPTION

Door handle

## AVAILABLE PRODUCTS

Product #	Color/Finish	Center to Center Drilling (Spacing)	Door Type	Door Thickness	Height	Screw/Nail
87H2R1002512170	Stainless Steel	12 in	Glass / Wood / Architectural	1 3/8 to 1 31/32 in*	16 in	Included / M8
87H2R1002524170	Stainless Steel	24 in	Glass / Wood / Architectural	1 3/8 to 1 31/32 in*	32 in	Included / M8
87H2R1002524171	Chrome / Polished Stainless Steel	24 in	Glass		31 1/2 in	Included / M6

## TECHNICAL SPECIFICATIONS

<b>Diameter</b>	31/32 in*
<b>Glass Thickness</b>	5/16 to 15/32 in*
<b>Projection</b>	2 3/8 in*
<b>Material</b>	Stainless Steel 316
<b>Type</b>	Round
<b>Washers Diameter</b>	1 3/32 in*
<b>Usage</b>	Sliding Door, Hinge Door, Commercial Door
<b>Milling Diameter</b>	9/16 in*
<b>Function</b>	Back-to-Back Pull Handle

### Disclaimer

Measures shown with an asterisk (\*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

## IMPORTANT INFORMATION

This illustration is provided for visual reference only. Actual product may vary. Order hardware before starting the job. The manufacturer reserves the right to change product and information without notice. Always follow the instructions inside the package. Drawings and technical documents contain examples of hardware from different manufacturers. The customer may not in any case make a claim following the use of these documents. The Company disclaims any responsibility for the structural details related to a construction or project. Installation must always be done by qualified personnel. Make sure that the product is properly installed using suitable fixtures on the support material. Never exceed the maximum load or size recommended by the manufacturer. Never use a spray lubricant on this product. Clean with a soft cloth and soap that is ammonia-free and nonabrasive. Always use a dry cloth to remove debris, dust and residues (sawdust and/or aluminum dust) from rails before installing hangers.

## DISCLAIMER

The preceding information, as well as any technical recommendation given in writing or verbally, whether based on tests or not, is provided to the best of our knowledge. Recommendations are non-binding and do not diminish your responsibility for determining the correctness of these recommendations and the suitability of the product for your particular purpose. The application, use or processing of our products, as well as the execution of projects based on our technical recommendations are beyond our control and therefore exclusively your responsibility. Sales of our products are subject to our most recent General Sales and Delivery Conditions. Please note that Richelieu will not accept any returns or claims for unpackaged products.

**PRODUCT PHOTOS**

