



LAB Recessed Profile

Finish



Packaging format

Length	Length

DESCRIPTION

Aluminum profile with anti-glare flap for recessed LED installation

- Designed for recessed installation in a blind or through milled groove which is 15/32 in (12 mm) wide and 17/32 in (13 mm) deep
- Light projection is shielded from view and directed away toward the inside of the lit compartment

ADVANTAGES AND BENEFITS

- APEX lens, without dot effect - Customize your lengths as needed; profiles can be cut easily with a miter saw. - Its length can be adapted to your needs with minimum of 11 13/16 in (300 mm) and maximum of 79 in (2 m)

AVAILABLE PRODUCTS

Product #	Finish	Packaging format
4122079010	Aluminum	Length
4122079990	Black	Length



TECHNICAL SPECIFICATIONS

Mounting	Recessed
Luminaire	Rigid Linear
Location	Inside Cabinet, Under Cabinet, Closet, Furniture
Application	Kitchen, Office, Commercial, Furniture, Closet
Lighting	Ambience, Accent, Task, Functional
Length	78 3/4 in*
Height	1/2 in*
Material	Aluminum
Standards and Certifications	cULus
Function	Aluminum Profile
Lighting Type	LED
Group	LED Group A
Style	Contemporary, Functional
Width	15/32 in*

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, <u>click here</u>.

INCLUDED PRODUCT(S)

- 78 3/4 in (2 m) Lab LED profile - 78 3/4 in (2 m) polycarbonate Apex LED profile

APPLICATION

- Cabinets - Bookcases - Display cases - Decorative lighting

IMPORTANT INFORMATION

- LED tape light sold separately: only compatible with Flexyled HE6 PW (see Suggested Products) - End caps sold separately - Giuseppe Bavuso design

DISCLAIMER

LED tape light sold separately: only compatible with Flexyled HE6 PW: 166124XX- 166122XX. End caps sold separately.



PRODUCT PHOTOS





