



SLU-ELAN Lift System

DESCRIPTION

Sugatsune parallel swing lift-up stay.

*** Connecting bar not included (needed for installation). See available lengths below.

ADVANTAGES AND BENEFITS

 - Lift assist mechanism for extra light opening - Door stays in any desired position -Damper equipped for soft and silent closing at the end - Simple installation by mounting guide plate and slide in main body - No hinges required - Connecting bar stays on top for maximum access inside the cabinet

AVAILABLE PRODUCTS

_	ro				- 11
_	ra		11	\sim t	т
	II W	ш	u	Uι	T

SLUELANH4

TECHNICAL SPECIFICATIONS

Brand	Sugatsune		
Door Type	Wood Door		
Door Height	15 3/8 to 19 5/8 in*		
Door Weight	21.2 to 24.3 lb*		
Opening Types	Parallel Opening		
Door Length	59 in*		

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, click here.

IMPORTANT INFORMATION

Minimum inside cabinet height is 14 13/16 in (360 mm) Door weight includes handle Recommended door size and weight: - Max width: 59 in (1500 mm) - Height: 15 3/8 in to 19 11/16 in (390 mm to 500 mm) per door - Weight: 11 lb to 24.2 lb (5 kg to 11 kg) per door *** Connecting bar not included (see required products) ***



PRODUCT PHOTOS







