



## LED Tape 9.6 W/m 24 V

### Light Color

Neutral White

Warm White

### Kelvin Color Temperature (K)

3000 K

4100 K

## DESCRIPTION

**Flexible LED tape with high output. Ideal for recessed aluminum profiles.**

This LED tape comes in 198 in (5 m) rolls and can be shortened every six LEDs.

- Can be cut every 50 mm or every six LEDs
- Can be applied onto any surface, 3M adhesive
- Beam angle: 120°

## ADVANTAGES AND BENEFITS

- Lifespan: 50 000 hrs - Easy installation, just peel and stick - Compatible with Richelieu 24 V system - Compatible with Richelieu profiles (see Suggested Products)

## AVAILABLE PRODUCTS

Product #	Light Color	Kelvin Color Temperature (K)
<b>30142496124</b>	Neutral White	4100 K
<b>30142496122</b>	Warm White	3000 K

## TECHNICAL SPECIFICATIONS

Location	Inside Cabinet, Under Cabinet, Furniture, Countertop
Application	Kitchen, Commercial, Furniture, Closet
Mounting	Surface
Luminaire	Flexible Linear
Compatibility	Micro 24
Lighting	Accent
Standards and Certifications	cULus
CRI (Color Rendering Index)	90
Luminous Efficiency	80.12 lm/W
Length	16 ft 4 in*
Height	1/16 in*
Width	5/16 in*
IP	IP22
Lighting Type	LED
Tension (V)	24 V
Watts	48 W
Group	LED Group A
Connection Type	Micro 24
Luminous Flux	234.5 Lumen
Features	Dimmable

### Disclaimer

Measures shown with an asterisk (\*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

## IMPORTANT INFORMATION

- 36.6 LED/ft, 120 LED/m, 600 LED/roll total - Rated power: 2.9 W/ft, 9.6 W/m, 48 W/roll total - We recommend a maximum length of 10 m or 96 W

## APPLICATION

- Countertops - Cabinets - Bookcases - Display cases

## DISCLAIMER

- Product information is subject to change - Do not bend where welded - Do not make the LED strip turn on itself - Do not bend LED strip - Wattage calculation for power supplies should be using an 80% maximum yield - Please contact the special orders desk for any special requests

**PRODUCT PHOTOS**

