



# LED Tape 4.8 W/m 24 V

### Light Color

Neutral White Warm White

# Kelvin Color Temperature (K)

3000 K	4100 K
--------	--------

### **Luminous Efficiency**

80 lm/W 82 lm/W

# DESCRIPTION

#### Flexible LED tape with high intensity for accent lighting

- This LED tape comes in 198 in (5 m) rolls and can be shortened every six LEDs
- Fits in Richelieu profiles
- Can be cut every six LED lights, or 3 15/16 in (100 mm) for 4.8 watts

# **ADVANTAGES AND BENEFITS**

- Easy installation, just peel and stick - Can be applied onto any surface, 3M adhesive - Lifespan: 50 000 hours - Highly resistant double-sided adhesive for fast installation - Compatible with Richelieu 24 V system - Compatible with Richelieu profiles (see Suggested Products)

# **AVAILABLE PRODUCTS**

Product #	Light Color	Kelvin Color Temperature (K)	Luminous Efficiency
30142448124	Neutral White	4100 K	80 lm/W
30142448122	Warm White	3000 K	82 lm/W



# **TECHNICAL SPECIFICATIONS**

Location	Inside Cabinet, Under Cabinet, Furniture, Countertop
Application	Kitchen, Commercial, Furniture
Mounting	Surface
Luminaire	Flexible Linear
Lighting	Accent
Standards and Certifications	cULus
CRI (Color Rendering Index)	90
Length	16 ft 4 in*
Height	1/16 in*
Width	5/16 in*
IP	IP22
Lighting Type	LED
Tension (V)	24 V
Watts	24 W
Group	LED Group A

#### Disclaimer

Measures shown with an asterisk (\*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, <u>click here</u>.

# **IMPORTANT INFORMATION**

- Can be cut every six LED lights, or 3 15/16 in (100 mm) for 4.8 watts - 18.3 LED/ft, 60 LED/m, 300 LED/roll total - Rated power: 1.5 W/ft or 4.8 W/m, 24 W/roll total - We recommend a maximum length of 10 m or 96 W

# **INCLUDED PRODUCT(S)**

- Flexible LED tape light with 3M TM adhesive tape

# DISCLAIMER

- Product information is subject to change - Do not bend where welded - Do not make the LED strip turn on itself - Do not bend LED strip - Wattage calculation for power supplies should be using an 80% maximum yield - Please contact the special orders desk for any special requests



# PRODUCT PHOTOS

