



Tubular Handle, Single Mount Ladder Type

Center to Center Drilling (Spacing)

12 in

24 in

36 in

48 in

Height

24 in

36 in

48 in

60 in

DESCRIPTION

Single ladder handle with locking washer

AVAILABLE PRODUCTS

Product #	Center to Center Drilling (Spacing)	Height
705241232SS170	12 in	24 in
705362432SS170	24 in	36 in
705483632SS170	36 in	48 in
705604832SS170	48 in	60 in

TECHNICAL SPECIFICATIONS

Color/Finish	Stainless Steel
Diameter	1 1/4 in*
Door Type	Glass, Wood, Architectural
Glass Thickness	5/16 to 15/32 in*
Door Thickness	1 3/8 to 1 31/32 in*
Projection	3 7/32 in*
Material	Stainless Steel 316
Type	Round
Washers Diameter	1 1/4 in*
Usage	Sliding Door, Hinge Door, Commercial Door
Milling Diameter	9/16 in*
Function	Single Pull Handle
Screw/Nail	Included, M8

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

APPLICATION

Ideal for use on glass or wood doors of commercial applications such as shopping malls and offices

INCLUDED PRODUCT(S)

Joints, fittings and fasteners.

IMPORTANT INFORMATION

Use safety glass! The glass must be shaped according to the section plane provided in the box. This illustration is provided for visual reference only. Actual product may vary. Order hardware before starting the job. Always follow the instructions inside the package. The manufacturer reserves the right to change product and information without notice. Installation must always be done by qualified personnel. Make sure that the product is properly installed using suitable fixtures on the support material. Never exceed the maximum load or size recommended by the manufacturer. The Company disclaims any responsibility for the structural details related to a construction or project.

DISCLAIMER

The preceding information, as well as any technical recommendation given in writing or verbally, whether based on tests or not, is provided to the best of our knowledge. Recommendations are non-binding and do not diminish your responsibility for determining the correctness of these recommendations and the suitability of the product for your particular purpose. The application, use or processing of our products, as well as the execution of projects based on our technical recommendations are beyond our control and therefore exclusively your responsibility. Sales of our products are subject to our most recent General Sales and Delivery Conditions. Please note that Richelieu will not accept any returns or claims for unpackaged products.

PRODUCT PHOTOS

