



Terno Solo Vetro 80 Sliding Glass Door System

Detailed Door Movement

Biparting

Single sliding

Overall Length

78 3/4 in*

13 ft 1 in*

Track type

Fixed Glass Panels

Standard

Number of Doors

1

2

Door Width

23 5/8 to 39 3/8 in*

23 5/8 to 47 1/4 in*

DESCRIPTION

Dry-glazing clamping shoe requires no glass drilling or adhesive

The Terno Solo Vetro 80 is a sliding glass door system for single sliding of glass doors and sliding partitions with fixed glass panels. Made for glass doors 5/16 in to 1/2 in (8 mm to 12.7 mm) thick, weighing up to 176 lb (80 kg) each.

- Hardware sets include soft self-closing mechanisms with anti-derail devices
- Concealed dry-glazing clamping shoe requires no drilling of the glass
- Flex-Mount upper track can be ceiling or wall mounted, as well as track options for sliding doors with fixed glass panels
- Clip-on fascia to cover clamping shoes and track
- Rubber press-on gaskets for fixed glass panels, no adhesive required
- Optional Synchro hardware sets for biparting applications with a durable pulley cable system linking two doors to open and close together in opposite directions

The Terno Solo Vetro 80 is an ideal solution for commercial and residential applications, meeting rooms, office partitions, and transaction counters in public spaces.

ADVANTAGES AND BENEFITS

Quick and simple low-cost installation

AVAILABLE PRODUCTS

Product #	Detailed Door Movement	Overall Length	Track type	Number of Doors	Door Width
WEBKIT1220358	Biparting	13 ft 1 in*	Fixed Glass Panels	2	23 5/8 to 47 1/4 in*
WEBKIT1220356	Biparting	13 ft 1 in*	Standard	2	23 5/8 to 47 1/4 in*
WEBKIT1220357	Single sliding	78 3/4 in*	Fixed Glass Panels	1	23 5/8 to 39 3/8 in*
WEBKIT1220355	Single sliding	78 3/4 in*	Standard	1	23 5/8 to 39 3/8 in*

TECHNICAL SPECIFICATIONS

Door Material	Glass
Door Movement	Straight Sliding
Track Mounting	Ceiling Mount, Wall Mount
Load Capacity	Max. 176 lb*
Door Thickness	5/16 to 1/2 in*
Brand	Terno
Finish	Anodized Silver
Soft-Closing	Yes
Soft-Close Type	One-Way Operation
Displayed in These Showrooms	New York, Dallas, Fort Meyers, Nashville
Door Height	Max. 9 ft*

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

IMPORTANT INFORMATION

- Pictures provided for visual reference only: actual product may vary. - All required hardware should be ordered and obtained prior to initiating fabrication or installation work. Please verify that the parts and quantities listed in your order are correct before proceeding to checkout. - Always use instructions provided by the manufacturer, as included with the product. Manufacturer reserves the right to amend, modify, or otherwise supplement any previously issued product and/or technical information, as deemed required from time to time, without prior notice. - The documentation, drawings, and instructions on this page apply to the system described on this page only. Richelieu expressly declines all responsibility for any design or construction that combines this system with systems from this same manufacturer or systems from other manufacturers. - Installation of the product shall be executed by qualified individuals only, always ensuring that each product is securely installed using proper fixation methods, as appropriate for each applicable substratum. We trust that anyone installing these products has the required skills, knowledge, and experience. Richelieu expressly disclaims any liabilities for results obtained through improper use or installation. - Always remove debris/dust/residues (sawdust and/or aluminum) from all tracks and guide channels using a dry cloth during installation and before operating the system. - Never spray lubricant.

DISCLAIMER

By accessing or referring to this document, or by using any of Richelieu's websites, you accept all applicable terms as they apply from time to time. This legal disclaimer is in no way limited or altered by any other terms or conditions. Richelieu may change said terms at its discretion and without prior notice. A version of the most current terms will always be available on Richelieu's website. The preceding information and technical documentation, information, or recommendations issued by Richelieu verbally or in writing is believed to be accurate and is given in good faith, but no representation of warranty as to its completeness or accuracy is made. Suggestions for use or application are only opinions. Users are responsible for determining the suitability of these products for their own particular purpose. No representation of warranty, expressed or implied, is made with respect to information or products including, without limitation, warranties or merchantability, fitness for particular purpose, non-infringement of any third party patent or other intellectual property rights including, without limit, copyright, trademark, and designs. Any trademarks identified herein are trademarks of the Richelieu group of companies. Richelieu assumes no risk and shall not be subject to any liability for damages or loss resulting from the specific use or application made of the product. Richelieu's liability for any claim, whether based on breach of contract, negligence, or infringement of any rights of any party relating to the product shall not exceed the price paid for said products. In no event shall Richelieu be liable for any special, incidental, or consequential damages (including loss of use, loss of profit, and claims of third parties) however caused, whether by the negligence of Richelieu or otherwise. Products returned for warranty purposes shall be subject to Richelieu's then applicable Return Policy.

PRODUCT PHOTOS

