



Grant TopLine 1200 Series Sliding Door System

Detailed Door Movement

Biparting

Single sliding

Load Capacity

Max. 225 lb*

Max. 324 lb*

Overall Length

72 in*

96 in*

11 ft 11 in*

12 ft*

15 ft 11 in*

Grant TopLine Model

Grant
TopLine 1210

Grant
TopLine 1230

Door Width

24 to 36 in*

24 to 48 in*

24 to 72 in*

30 to 36 in*

30 to 48 in*

30 to 72 in*

DESCRIPTION

For heavy and tall wood doors

The Grant TopLine 1200 Series Sliding Door System, featuring the Grant TopLine 1210 and Grant TopLine 1230, is designed for wood doors at least 1 in (25.4 mm) thick.

- Precision ball bearing wheel trolleys
- Heavy-duty double aluminum I-BEAM track
- Surface top-mount suspension plate
- Suitable for single and biparting door applications

These top-mount systems are designed for commercial and residential use. An ideal solution for partition walls, room dividers, and heavy or large doors.

ADVANTAGES AND BENEFITS

- Jump-proof design - Smooth, quiet, and long-lasting performance - Adjustable - ANSI-BHMA compliant

AVAILABLE PRODUCTS

Product #	Detailed Door Movement	Load Capacity	Overall Length	Grant TopLine Model	Door Width
WEBKIT1248303	Biparting	Max. 225 lb*	11 ft 11 in*	Grant TopLine 1210	24 to 36 in*
WEBKIT1224360	Biparting	Max. 324 lb*	15 ft 11 in*	Grant TopLine 1230	30 to 72 in*
WEBKIT1220463	Single sliding	Max. 225 lb*	72 in*	Grant TopLine 1210	24 to 36 in*
WEBKIT1220464	Single sliding	Max. 225 lb*	96 in*	Grant TopLine 1210	24 to 48 in*
WEBKIT1220466	Single sliding	Max. 225 lb*	12 ft*	Grant TopLine 1210	24 to 72 in*
WEBKIT1220468	Single sliding	Max. 324 lb*	72 in*	Grant TopLine 1230	30 to 36 in*
WEBKIT1220469	Single sliding	Max. 324 lb*	96 in*	Grant TopLine 1230	30 to 48 in*
WEBKIT1220471	Single sliding	Max. 324 lb*	12 ft*	Grant TopLine 1230	30 to 72 in*

TECHNICAL SPECIFICATIONS

Door Material	Wood
Door Movement	Straight Sliding
Track Mounting	Ceiling Mount
Door Thickness	Min. 1 in*
Brand	Grant Hettich
Soft-Closing	No
Standards and Certifications	ANSI/BHMA Grade 1
Door Height	Max. 9 ft*

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

IMPORTANT INFORMATION

- A continuous floor guide is recommended for doors wider than 44 in (1 100 mm). - Pictures provided for visual reference only: actual product may vary. - All required hardware should be ordered and obtained prior to initiating fabrication or installation work. Please verify that the parts and quantities listed in your order are correct before proceeding to checkout. - Always use instructions provided by the manufacturer, as included with the product. Manufacturer reserves the right to amend, modify, or otherwise supplement any previously issued product and/or technical information, as deemed required from time to time, without prior notice. - The documentation, drawings, and instructions on this page apply to the system described on this page only. Richelieu expressly declines all responsibility for any design or construction that combines this system with systems from this same manufacturer or systems from other manufacturers. - Installation of the product shall be executed by qualified individuals only, always ensuring that each product is securely installed using proper fixation methods, as appropriate for each applicable substratum. We trust that anyone installing these products has the required skills, knowledge, and experience. Richelieu expressly disclaims any liabilities for results obtained through improper use or installation. - Always remove debris/dust/residues (sawdust and/or aluminum) from all tracks and guide channels using a dry cloth during installation and before operating the system. - Never spray lubricant.

DISCLAIMER

By accessing or referring to this document, or by using any of Richelieu's websites, you accept all applicable terms as they apply from time to time. This legal disclaimer is in no way limited or altered by any other terms or conditions. Richelieu may change said terms at its discretion and without prior notice. A version of the most current terms will always be available on Richelieu's website. The preceding information and technical documentation, information, or recommendations issued by Richelieu verbally or in writing is believed to be accurate and is given in good faith, but no representation of warranty as to its completeness or accuracy is made. Suggestions for use or application are only opinions. Users are responsible for determining the suitability of these products for their own particular purpose. No representation of warranty, expressed or implied, is made with respect to information or products including, without limitation, warranties or merchantability, fitness for particular purpose, non-infringement of any third party patent or other intellectual property rights including, without limit, copyright, trademark, and designs. Any trademarks identified herein are trademarks of the Richelieu group of companies. Richelieu assumes no risk and shall not be subject to any liability for damages or loss resulting from the specific use or application made of the product. Richelieu's liability for any claim, whether based on breach of contract, negligence, or infringement of any rights of any party relating to the product shall not exceed the price paid for said products. In no event shall Richelieu be liable for any special, incidental, or consequential damages (including loss of use, loss of profit, and claims of third parties) however caused, whether by the negligence of Richelieu or otherwise. Products returned for warranty purposes shall be subject to Richelieu's then applicable Return Policy.

PRODUCT PHOTOS

