



# **AVENTOS HK Top with SERVO-DRIVE Kits**

## **Door Type**

Narrow Aluminum-Framed Door (20 mm and Less)

Thin Door

Wood Door / Wide Aluminum-Framed Door

### **Power Factor**

420 to 1 270

1 271 to 2 265

2 266 to 4 200

4 201 to 9 000

### **DESCRIPTION**

Effortless opening and smooth closing for pivot-opening doors. Ideal for small cabinets or cupboards. Designed for doors with a maximum width of 70 in (1.7 m) and height from 8 in to 23 in (203 mm to 584 mm).

#### **ADVANTAGES AND BENEFITS**

- An innovative mechanism prevents the lever arm from inadvertently folding in for added security. - Two different opening mechanisms are available: with positioning template or with pre-mounted screws (reversible).

#### **AVAILABLE PRODUCTS**

| Product #     | Door Type                                    | Power Factor   |
|---------------|--|----------------|
| WEBKIT1231629 | Narrow Aluminum-Framed Door (20 mm and Less) | 420 to 1 270   |
| WEBKIT1231631 | Narrow Aluminum-Framed Door (20 mm and Less) | 1 271 to 2 265 |
| WEBKIT1231633 | Narrow Aluminum-Framed Door (20 mm and Less) | 2 266 to 4 200 |
| WEBKIT1231634 | Narrow Aluminum-Framed Door (20 mm and Less) | 4 201 to 9 000 |
| WEBKIT1231636 | Thin Door                                    | 420 to 1 270   |
| WEBKIT1231638 | Thin Door                                    | 1 271 to 2 265 |
| WEBKIT1231640 | Thin Door                                    | 2 266 to 4 200 |
| WEBKIT1231642 | Thin Door                                    | 4 201 to 9 000 |
| WEBKIT1231621 | Wood Door / Wide Aluminum-Framed Door        | 420 to 1 270   |
| WEBKIT1231623 | Wood Door / Wide Aluminum-Framed Door        | 1 271 to 2 265 |
| WEBKIT1231625 | Wood Door / Wide Aluminum-Framed Door        | 2 266 to 4 200 |
| WEBKIT1231627 | Wood Door / Wide Aluminum-Framed Door        | 4 201 to 9 000 |



### **TECHNICAL SPECIFICATIONS**

| Brand                                   | Blum                 |
|---|----------------------|
| Finish                                  | Light Gray           |
| Minimum internal depth of the enclosure | 7 3/8 in*            |
| Door Height                             | 8 1/16 to 23 5/8 in* |
| Opening Types                           | Lift-Up Opening      |
| Servo Drive                             | Included             |
| Screw/Nail                              | Positioning Template |
| Hinge Opening Angle                     | +107°                |

#### **Disclaimer**

Measures shown with an asterisk (\*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, <u>click here</u>.

### IMPORTANT INFORMATION

Please consult the supplier's documents in order to properly calculate the Power factor (LF) required for your project. Always round up to the highest number for your selection. Formula: (LF) = Cabinet height (KH) mm x Front weight including double handle weight (kg)

# **INCLUDED PRODUCT(S)**

Each set includes: - 1 pair of AVENTOS HK top mechanism - 1 set of covers for AVENTOS HK top opening mechanism - 1 set of fixing brackets - 1 SERVO-DRIVE unit

### **PRODUCT PHOTOS**

