



FlexyLED HE6B PW PRO 24 V

Light Color

Neutral White

Warm White

Kelvin Color Temperature (K)

3000 K

4000 K

Length

19 5/8 in*

78 3/4 in*

Watts

5 W

20 W

DESCRIPTION

Flexible pre-wired LED modules to be integrated

FlexyLED HE6B PW is an LED strip with 120 LED/m on a circuit only 6 mm wide. It is supplied with a high adherence 3M® adhesive base so it can be installed into profiles with a removable diffuser. These modules are designed with reinforced soldered power supply cable terminals which ensure good solidity.

ADVANTAGES AND BENEFITS

- Pre-wired collection features modules with varying lengths - Supplied with power cable, and ready to be installed without the need for complicated soldering - Supplied with a high adherence 3M® adhesive - Surface or integrated into profiles - Reinforced solder power supply cable terminals - Can be cut every 1 in (25 mm) - 9.6 W/m - Compatible with Apex, Miss, Lab, and Blade - 120 LEDs/meter

AVAILABLE PRODUCTS

| Product # | Light Color | Kelvin Color Temperature (K) | Length | Watts |
|-------------------|---------------|------------------------------|------------|-------|
| 1661242000 | Neutral White | 4000 K | 78 3/4 in* | 20 W |
| 166122500 | Warm White | 3000 K | 19 5/8 in* | 5 W |
| 1661222000 | Warm White | 3000 K | 78 3/4 in* | 20 W |

TECHNICAL SPECIFICATIONS

| | |
|------------------------------|------------------------------------------|
| Location | Inside Cabinet, Under Cabinet, Furniture |
| Application | Kitchen, Office, Furniture, Closet |
| Mounting | Surface |
| Luminaire | Flexible Linear |
| Compatibility | Micro 24 |
| Lighting | Ambience, Accent |
| Standards and Certifications | UL |
| Style | Contemporary |
| CRI (Color Rendering Index) | 80 |
| Luminous Efficiency | 82 lm/W |
| IP | IP20 |
| Lighting Type | LED |
| Tension (V) | 24 V |
| Group | LED Group A |
| Watts/Foot | 2.93 W |
| Connection Type | Micro 24 |
| Features | Dimmable |

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

INCLUDED PRODUCT(S)

- Pre-wired 78 23/32 in (2000 mm) cable with Micro 24 connector

PRODUCT PHOTOS

