



CavitySliders CS Hardware Set

Stopper

One

Two

Load Capacity

40 to 200 lb

200 to 500 lb

DESCRIPTION

CarriSnap mounting plate

The Cavity Sliders CS hardware sets are designed for sliding wood doors weighing up to 500 lb (227 kg) each.

- Features:
- Two types of carriage/hardware sets to choose from: M6 for 200 lb (90 kg) and M8 for 500 lb (227 kg) doors
 - Select from hardware sets with one or two track stops
 - CarriSnap mounting suspension plate for the top of the door for mounting and releasing the upper trolley without tools
 - Large wheel trolleys with precision ground bearings for smooth running
 - Simple and flexible low-cost installation

ADVANTAGES AND BENEFITS

- CarriSnap mounting suspension plate for the top of the door for mounting and releasing the upper trolley without tools
- Large wheel trolleys with precision ground bearings for smooth running
- Simple and flexible low-cost installation

AVAILABLE PRODUCTS

Product #	Stopper	Load Capacity
DKM0611	One	40 to 200 lb
DKM0811	One	200 to 500 lb
DKM0621	Two	40 to 200 lb
DKM0821	Two	200 to 500 lb

TECHNICAL SPECIFICATIONS

Door Movement	Straight Sliding
Detailed Door Movement	Single sliding
Door Position	Inset/Inlay
Roller Position	Upper
Door Installation	Top Hung
Running Track Fixing	Surface and Recessed
Packaging Format	Box
Thickness	1 3/8 to 2 in
Compatible with	CS Door Collection, Cavity Sliders
Adjustable	Yes
Manufacturing Material	Metal, Steel, and Nylon
Drilling Depth	0.5 in
Drilling	1 in
Roller Type	Ball Bearing
Product type	Hardware Set
Door Material	Wood
Number of Doors	1
Track type	Box Track
Door Width	25 to 71 in
Door Thickness	1 3/8 to 1 3/4 in
Door Height	120 in
Soft-Closing	No
Brand	Cavity Sliders
Application	Standard Access Door

INCLUDED PRODUCT(S)

- Upper trolleys - CarriSnap mounting suspension plate - Track stopper - Floor guide - Adjustment tool - Screws and fasteners for individual components only

IMPORTANT INFORMATION

Please make sure to read the entirety of the installation manual before proceeding with the installation. A groove is required for the bottom of the door for the floor guide, see instructions. Always remove debris/dust/residues (sawdust and/or aluminum) from all tracks and guide channels using a dry cloth during installation and before operating the system. Never spray lubricant on this product. Do not exceed stated limitations and parameters. This will cause early wear and performance failure.

DISCLAIMER

Please make sure to read the entirety of the installation manual before proceeding with the installation. A groove is required for the bottom of the door for the floor guide, see instructions. Wear safety gear such as gloves, safety glasses, safety shoes, and ear protection. Do not exceed stated limitations and parameters. This will cause early wear and performance failure, and will void the warranty. - Pictures provided for visual reference only: actual product may vary. - All required hardware should be ordered and obtained prior to initiating fabrication or installation work. Please verify that the parts and quantities listed in your order are correct before proceeding to checkout. - Always use instructions provided by the manufacturer, as included with the product. Manufacturer reserves the right to amend, modify, or otherwise supplement any previously issued product and/or technical information, as deemed required from time to time, without prior notice. - The documentation, drawings, and instructions on this page apply to the system described on this page only. Richelieu expressly declines all responsibility for any design or construction that combines this system with systems from this same manufacturer or systems from other manufacturers. - Installation of the product shall be executed by qualified individuals only, always ensuring that each product is securely installed using proper fixation methods, as appropriate for each applicable substratum. We trust that anyone installing these products has the required skills, knowledge, and experience. Richelieu expressly disclaims any liabilities for results obtained through improper use or installation. - Always remove debris/dust/residues (sawdust and/or aluminum) from all tracks and guide channels using a dry cloth during installation and before operating the system. - Never spray lubricant on this product.

PRODUCT PHOTOS

