



Cielo - Horizontal Opening Mechanism With Concealed Legs

Mattress Size



Static Load Rating

331 lb*	441 lb*

Height of the Leg

11 1/4 in* 14 1/8 in*

Required Interior Dimensions - Width

78 5/8 in*	83 3/4 in*

DESCRIPTION

More Richelieu innovation with this folding bed set.

Parallel-to-wall bed with auto-deployment of hidden feet on both sides of the door. Can house a mattress that is 7 in (180 mm) to 13 in (330 mm) thick.

ADVANTAGES AND BENEFITS

- You can install a mattress that is thicker than the standard 7 in (180 mm) by building a deeper unit - High load-capacity of 441lb (200kg) allows large and small people to sleep easy - Latest generation of piston offers smooth and secure opening and closing (Required item) - High-quality slatted frame screws directly to the door panel - Ideal for small spaces - 5/8 in (15 mm) leg with adjustable leveler

AVAILABLE PRODUCTS

Product #	Mattress Size	Static Load Rating	Height of the Leg	Required Interior Dimensions - Width
8410014	Double (54 in x 75 in)	441 lb*	11 1/4 in*	78 5/8 in*
8412014	Double (54 in x 75 in)	441 lb*	14 1/8 in*	78 5/8 in*
8410016	Queen (60 in x 80 in)	441 lb*	11 1/4 in*	83 3/4 in*
8412016	Queen (60 in x 80 in)	441 lb*	14 1/8 in*	83 3/4 in*
8410012	Single (39 in x 75 in)	331 lb*	11 1/4 in*	78 5/8 in*



TECHNICAL SPECIFICATIONS

Opening	Horizontal
Configuration	Concealed Leg
Finish	Matte Nickel
Material	Steel
Designer	G.Manzoni
Required Interior Dimension - Depth	11 in*

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, <u>click here</u>.

APPLICATION

Good for tight spaces, this multifunctional unit optimizes usable floor space.

INCLUDED PRODUCT(S)

Please refer to the "Hardware List" document. ***The cabinet is NOT included and must be built by the customer. *** ***The reinforcement bar acts as an optional component that can be purchased separately (see suggested products). ***

IMPORTANT INFORMATION

*** The customer MUST NOT use the legs or shelf to lower the door. The customer must use the handle previously installed on the door. ***

DISCLAIMER

Ensure unit is properly secured to wall. For a quality build, panel thickness must be 3/4 in (19 mm) or more.

PRODUCT PHOTOS















