



EVO Sliding Door System

Load Capacity

33.1 to 88.2
lb*

88.2 to 132 lb*

132 to 176 lb*


Overall Length

78 3/4 in*


9 ft 10 in*

13 ft 1 in*


Finish



Black (90)



Champagne



Chrome (140)



Titanium

Number of Doors

1

2

Door Width

27 1/2 to 39
3/8 in*

27 1/2 to 48
in*

DESCRIPTION

Can be applied to various surfaces

The EVO barn door style sliding system for wood or glass doors for three different weight capacities: 40 kg (88 lb), 60 kg (132 lb), and 80 kg (176 lb).

Features:

- For wood doors 19 mm (3/4 in) to 36 mm (1 3/8 in) thick
- For glass doors 8 mm (5/16 in) to 10 mm (3/8 in) thick
- Available in four finishes: black, chrome, champagne, and titanium
- Three choices of track lengths: 2 m (78 3/4 in), 3 m (118 in), and 4 m (157 in)
- Concealed soft-close mechanisms can be adjusted to different positions
- Bracket support mounts can be adjusted to different positions behind the track
- Choose from two sizes of matching SLIM pull handles with a self-adhesive back that can be applied to smooth surfaces such as wood, laminate, glass, steel, or aluminum
- Smooth operating
- Simple, flexible, and low-cost installation

IMPORTANT: The minimum door width with a soft-close mechanism is 700 mm (27 1/2 in).

Lighting may alter the appearance of some finishes and differ from the published renderings.

Ideal solution for residential and commercial applications for thin and thick doors, feature designer doors, walk-in closets, pantries, and standard access doors to a room.

ADVANTAGES AND BENEFITS

- Available in four finishes: black, chrome, champagne, and titanium - Three choices of

track lengths: 78 3/4 in (2 m), 118 in (3 m), and 156 in (4 m) - Concealed soft-close mechanisms can be adjusted to different positions - Bracket support mounts can be adjusted to different positions behind the track - Matching pull handle SLIM with self-adhesive back can be applied to different surfaces

AVAILABLE PRODUCTS

Product #	Load Capacity	Overall Length	Finish	Number of Doors	Door Width
WEBKIT1242838	33.1 to 88.2 lb*	78 3/4 in*	Black (90)	1	27 1/2 to 39 3/8 in*
WEBKIT1242829	33.1 to 88.2 lb*	78 3/4 in*	Champagne	1	27 1/2 to 39 3/8 in*
WEBKIT1242820	33.1 to 88.2 lb*	78 3/4 in*	Chrome (140)	1	27 1/2 to 39 3/8 in*
WEBKIT1242847	33.1 to 88.2 lb*	78 3/4 in*	Titanium	1	27 1/2 to 39 3/8 in*
WEBKIT1242841	33.1 to 88.2 lb*	9 ft 10 in*	Black (90)	1	27 1/2 to 48 in*
WEBKIT1242832	33.1 to 88.2 lb*	9 ft 10 in*	Champagne	1	27 1/2 to 48 in*
WEBKIT1242823	33.1 to 88.2 lb*	9 ft 10 in*	Chrome (140)	1	27 1/2 to 48 in*
WEBKIT1242850	33.1 to 88.2 lb*	9 ft 10 in*	Titanium	1	27 1/2 to 48 in*
WEBKIT1242844	33.1 to 88.2 lb*	13 ft 1 in*	Black (90)	2	27 1/2 to 39 3/8 in*
WEBKIT1242835	33.1 to 88.2 lb*	13 ft 1 in*	Champagne	2	27 1/2 to 39 3/8 in*
WEBKIT1242826	33.1 to 88.2 lb*	13 ft 1 in*	Chrome (140)	2	27 1/2 to 39 3/8 in*
WEBKIT1242853	33.1 to 88.2 lb*	13 ft 1 in*	Titanium	2	27 1/2 to 39 3/8 in*
WEBKIT1242839	88.2 to 132 lb*	78 3/4 in*	Black (90)	1	27 1/2 to 39 3/8 in*
WEBKIT1242830	88.2 to 132 lb*	78 3/4 in*	Champagne	1	27 1/2 to 39 3/8 in*
WEBKIT1242821	88.2 to 132 lb*	78 3/4 in*	Chrome (140)	1	27 1/2 to 39 3/8 in*
WEBKIT1242848	88.2 to 132 lb*	78 3/4 in*	Titanium	1	27 1/2 to 39 3/8 in*
WEBKIT1242842	88.2 to 132 lb*	9 ft 10 in*	Black (90)	1	27 1/2 to 48 in*
WEBKIT1242833	88.2 to 132 lb*	9 ft 10 in*	Champagne	1	27 1/2 to 48 in*
WEBKIT1242824	88.2 to 132 lb*	9 ft 10 in*	Chrome (140)	1	27 1/2 to 48 in*
WEBKIT1242851	88.2 to 132 lb*	9 ft 10 in*	Titanium	1	27 1/2 to 48 in*
WEBKIT1242845	88.2 to 132 lb*	13 ft 1 in*	Black (90)	2	27 1/2 to 39 3/8 in*
WEBKIT1242836	88.2 to 132 lb*	13 ft 1 in*	Champagne	2	27 1/2 to 39 3/8 in*
WEBKIT1242827	88.2 to 132 lb*	13 ft 1 in*	Chrome (140)	2	27 1/2 to 39 3/8 in*
WEBKIT1242854	88.2 to 132 lb*	13 ft 1 in*	Titanium	2	27 1/2 to 39 3/8 in*
WEBKIT1242840	132 to 176 lb*	78 3/4 in*	Black (90)	1	27 1/2 to 39 3/8 in*
WEBKIT1242831	132 to 176 lb*	78 3/4 in*	Champagne	1	27 1/2 to 39 3/8 in*
WEBKIT1242822	132 to 176 lb*	78 3/4 in*	Chrome (140)	1	27 1/2 to 39 3/8 in*
WEBKIT1242849	132 to 176 lb*	78 3/4 in*	Titanium	1	27 1/2 to 39 3/8 in*
WEBKIT1242843	132 to 176 lb*	9 ft 10 in*	Black (90)	1	27 1/2 to 48 in*
WEBKIT1242834	132 to 176 lb*	9 ft 10 in*	Champagne	1	27 1/2 to 48 in*
WEBKIT1242825	132 to 176 lb*	9 ft 10 in*	Chrome (140)	1	27 1/2 to 48 in*
WEBKIT1242852	132 to 176 lb*	9 ft 10 in*	Titanium	1	27 1/2 to 48 in*
WEBKIT1242846	132 to 176 lb*	13 ft 1 in*	Black (90)	2	27 1/2 to 39 3/8 in*
WEBKIT1242837	132 to 176 lb*	13 ft 1 in*	Champagne	2	27 1/2 to 39 3/8 in*
WEBKIT1242828	132 to 176 lb*	13 ft 1 in*	Chrome (140)	2	27 1/2 to 39 3/8 in*
WEBKIT1242855	132 to 176 lb*	13 ft 1 in*	Titanium	2	27 1/2 to 39 3/8 in*

TECHNICAL SPECIFICATIONS

Door Material	Wood, Glass
Door Movement	Straight Sliding
Detailed Door Movement	Single sliding
Track Mounting	Wall Mount
Door Thickness	5/16 to 1 13/32 in*
Roller Type	Premium Ball Bearing
Roller Position	Upper
Application	Standard Access Door, Barn Door
Screw/Nail Included	Yes
Height Clearance	7 17/32 in*
Running Track Fixing	Bracket
Manufacturing Material	Aluminum
Adjustable	Yes
Soft-Closing	Yes
Soft-Close Type	One-Way Operation
Displayed in These Showrooms	Toronto
Style	Barn Door
Groove Depth	1/2 in*
Groove Needed for Guiding System	Yes
Door Projection	3 5/32 in*
Door Installation	Top Hung
Door Height	Max. 8 ft 6 in*
Groove Width at the Bottom of Door	15/32 in*

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

IMPORTANT INFORMATION

- IMPORTANT: The minimum door width with soft-close mechanism is 27 1/2 in (700 mm). - Please make sure to read the entirety of the installation manual before proceeding with the installation. - Wear safety gear such as gloves, safety glasses, safety shoes, and ear protection. - Every fastener used to attach the track to the wall must be fastened securely into a structural surface. - Always remove debris/dust/residues (sawdust and/or aluminum) from all tracks and guide channels using a dry cloth during installation and before operating the system. - Never spray lubricant on this product. - Do not exceed stated limitations and parameters. This will cause early wear and performance failure, and will void the warranty.

APPLICATION

- For wood and glass doors

DISCLAIMER

Pictures provided for visual reference only: actual product may vary. - All required hardware should be ordered and obtained prior to initiating fabrication or installation work. Please verify that the parts and quantities listed in your order are correct before proceeding to checkout. - Always use instructions provided by the manufacturer, as included with the product. Manufacturer reserves the right to amend, modify, or otherwise supplement any previously issued product and/or technical information, as deemed required from time to time, without prior notice. - The documentation, drawings, and instructions on this page apply to the system described on this page only. Richelieu expressly declines all responsibility for any design or construction that combines this system with systems from this same manufacturer or systems from other manufacturers. - Installation of the product shall be executed by qualified individuals only, always ensuring that each product is securely installed using proper fixation methods, as appropriate for each applicable substratum. We trust that anyone installing these products has the required skills, knowledge, and experience. Richelieu expressly disclaims any liabilities for results obtained through improper use or installation.

PRODUCT PHOTOS





