



DAMA Hardware Set

Load Capacity

33.1 lb*

66.1 lb*

Door Material

Glass

Wood

Door Width

11 3/4 to 35 3/8 in*

11 3/4 to 39 3/8 in*

Door Thickness

5/32 to 1/4 in*

3/4 to 1 1/16 in*

Door Height

Max. 39 3/8 in*

Max. 70 7/8 in*

Max. 78 3/4 in*

DESCRIPTION

For wood and glass doors

The DAMA hardware set for one cabinet wood or glass door with weight capacity of 33 lb (15 kg) or 66 lb (30 kg).

Features:

- Bottom running system for inset applications
- Surface mount hardware for wood doors from 3/4 in (19 mm) to 1 1/16 in (27 mm) thick
- Patch fitting for glass doors 5/32 in (4 mm) to 7/32 in (6 mm) thick
- Includes track stoppers
- Track sold separately, available in silver or black
- Simple and flexible installation

IMPORTANT: Use metric dimensions for greater accuracy during installation. For glass, bore four holes with a 5/16 in (8 mm) diameter as per instructions.

ADVANTAGES AND BENEFITS

- For wood or glass doors, with weight capacity of 33 lb (15 kg) and 66 lb (30 kg) - Bottom running system for inset applications - Surface mount hardware for wood doors from 3/4 in (19 mm) to 1 in (27 mm) thick - Patch fitting for glass doors 5/32 in (4 mm) to 7/32 in (6 mm) thick - Includes track stoppers

AVAILABLE PRODUCTS

Product #	Load Capacity	Door Material	Door Width	Door Thickness	Door Height
189K1385	33.1 lb*	Glass	11 3/4 to 35 3/8 in*	5/32 to 1/4 in*	Max. 39 3/8 in*
189K1381	33.1 lb*	Wood	11 3/4 to 39 3/8 in*	3/4 to 1 1/16 in*	Max. 39 3/8 in*
189K1386	66.1 lb*	Glass	11 3/4 to 39 3/8 in*	5/32 to 1/4 in*	Max. 70 7/8 in*
189K1382	66.1 lb*	Wood	11 3/4 to 39 3/8 in*	3/4 to 1 1/16 in*	Max. 78 3/4 in*

TECHNICAL SPECIFICATIONS

Door Movement	Straight Sliding
Detailed Door Movement	Single sliding, Bypassing
Roller Position	Lower
Stopper	Two
Manufacturing Material	Nylon, Aluminum
Product type	Hardware Set
Number of Doors	1
Application	Furniture, Cabinet, Storage, Showcase

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

INCLUDED PRODUCT(S)

For wood doors: - 2 upper guides - 2 bottom running wheels - 2 stoppers - Screws and fasteners for individual components only
For glass doors: - 2 upper patch fittings with guides - 2 bottom patch fittings with running wheels - 2 stoppers - Screws and fasteners for individual components only

IMPORTANT INFORMATION

IMPORTANT: For glass, bore four holes with a 5/16 in (8 mm) diameter as per instructions. - Please make sure to read the entirety of the installation manual before proceeding with the installation. - Use metric dimensions for greater accuracy during installation. - Wear safety gear such as gloves, safety glasses, safety shoes, and ear protection. - Every fastener used to attach the track to the wall must be fastened securely into a structural surface. - Always remove debris/dust/residues (sawdust and/or aluminum) from all tracks and guide channels using a dry cloth during installation and before operating the system. - Never spray lubricant on this product. - Do not exceed stated limitations and parameters. This will cause early wear and performance failure, and will void the warranty.

DISCLAIMER

Pictures provided for visual reference only: actual product may vary. - All required hardware should be ordered and obtained prior to initiating fabrication or installation work. Please verify that the parts and quantities listed in your order are correct before proceeding to checkout. - Always use instructions provided by the manufacturer, as included with the product. Manufacturer reserves the right to amend, modify, or otherwise supplement any previously issued product and/or technical information, as deemed required from time to time, without prior notice. - The documentation, drawings, and instructions on this page apply to the system described on this page only. Richelieu expressly declines all responsibility for any design or construction that combines this system with systems from this same manufacturer or systems from other manufacturers. - Installation of the product shall be executed by qualified individuals only, always ensuring that each product is securely installed using proper fixation methods, as appropriate for each applicable substratum. We trust that anyone installing these products has the required skills, knowledge, and experience. Richelieu expressly disclaims any liabilities for results obtained through improper use or installation.

PRODUCT PHOTOS

