


TYPE 710



TYPE 710 Aluminum Double Track

Overall Length

78 3/4 in*	9 ft 10 in*	13 ft 1 in*
------------	-------------	-------------

DESCRIPTION

Silver anodized

The TYPE 710 aluminum double track is designed for the SCORRI FLAT cabinet, wardrobe, and closet door sliding system. It is surface mounted to the top of the cabinet or door opening. Can be installed next to TYPE 711 aluminum single track for triple bypassing door applications.

Features:

- Available in silver anodized
- Three different lengths: 78 in (2 m), 118 in (3 m), and 156 in (4 m)
- Can be cut to suit application

IMPORTANT: Use metric dimensions for greater accuracy during installation.

ADVANTAGES AND BENEFITS

- Available in silver anodized - Three different lengths: 78 in (2 m), 118 in (3 m), and 156 in (4 m) - Can be cut to suit application

AVAILABLE PRODUCTS

Product #	Overall Length
189A710210	78 3/4 in*
189A710310	9 ft 10 in*
189A710410	13 ft 1 in*

TECHNICAL SPECIFICATIONS

Detailed Door Movement	Bypassing
Track type	Double Running
Compatible with	Scorri FLAT
Door Installation	Top Hung
Load Capacity	110 lb*
Manufacturing Material	Aluminum
Track Mounting	Wall Mount
Width	1 9/16 in*
Finish	Silver
Door Material	Wood
Pre-drilled	No
Door Movement	Straight Sliding
Door Thickness	5/8 to 25/32 in*
Product type	Running and Guiding Tracks
Overall Height	1 3/32 in*
Height Clearance	1 3/8 in*
Application	Closet and Walk-In Closet, Wardrobe, Cabinet, Storage

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

INCLUDED PRODUCT(S)

1 track

IMPORTANT INFORMATION

- Please make sure to read the entirety of the installation manual before proceeding with the installation. - Use metric dimensions for greater accuracy during installation. - Wear safety gear such as gloves, safety glasses, safety shoes, and ear protection. - Every fastener used to attach the track to the wall must be fastened securely into a structural surface. - Always remove debris/dust/residues (sawdust and/or aluminum) from all tracks and guide channels using a dry cloth during installation and before operating the system. - Never spray lubricant on this product. - Do not exceed stated limitations and parameters. This will cause early wear and performance failure, and will void the warranty.

DISCLAIMER

Pictures provided for visual reference only: actual product may vary. - All required hardware should be ordered and obtained prior to initiating fabrication or installation work. Please verify that the parts and quantities listed in your order are correct before proceeding to checkout. - Always use instructions provided by the manufacturer, as included with the product. Manufacturer reserves the right to amend, modify, or otherwise supplement any previously issued product and/or technical information, as deemed required from time to time, without prior notice. - The documentation, drawings, and instructions on this page apply to the system described on this page only. Richelieu expressly declines all responsibility for any design or construction that combines this system with systems from this same manufacturer or systems from other manufacturers. - Installation of the product shall be executed by qualified individuals only, always ensuring that each product is securely installed using proper fixation methods, as appropriate for each applicable substratum. We trust that anyone installing these products has the required skills, knowledge, and experience. Richelieu expressly disclaims any liabilities for results obtained through improper use or installation.

PRODUCT PHOTOS

TYPE 710

