



## TERNO VETRO 40 Hardware Sets

### Load Capacity

88.2 to 176 lb*	179 to 265 lb*
-----------------	----------------

### DESCRIPTION

#### Low pull force

The TERNO VETRO 40 hardware sets with FLUID soft-close mechanism is designed for one glass door for door weight capacities of 176 lb (80 kg) and 264 lb (120 kg).

#### Features:

- Clip-on suspension plate to mount the door without tools
- For glass thickness of 5/16 in (8 mm) to 1/2 in (12.7 mm)
- Two soft-close mechanisms with FLUID technology
- Low pull force to open the door
- All hardware sets operate on the same tracks
- Simple and flexible installation
- Smooth operating

**IMPORTANT:** Use metric dimensions for greater accuracy during installation. Clamping shoe sold separately.

### ADVANTAGES AND BENEFITS

- Clip-on suspension plate to mount the door without tools
- For glass thickness of 5/16 in (8 mm) to 1/2 in (12.7 mm)
- Two soft-close mechanisms with FLUID technology
- Low pull force to open the door
- All hardware sets operate on the same tracks

### AVAILABLE PRODUCTS

Product #	Load Capacity
89K03246	88.2 to 176 lb*
89K03256	179 to 265 lb*

## TECHNICAL SPECIFICATIONS

Door Movement	Straight Sliding
Detailed Door Movement	Single sliding
Roller Position	Upper
Door Installation	Top Hung
Manufacturing Material	Nylon, Aluminum, Plastic
Roller Type	Ball Bearing
Product type	Hardware Set
Door Material	Glass
Number of Doors	1
Door Width	29 1/8 to 47 1/4 in*
Door Thickness	13/32 to 1/2 in*
Door Height	8 ft 10 in*
Soft-Closing	Yes
Soft-Close Type	FLUID
Application	Standard Access Door

### Disclaimer

Measures shown with an asterisk (\*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

## INCLUDED PRODUCT(S)

- 2 upper wheels with suspension bolts - 2 clip-on suspension plates - 2 soft-close mechanisms - 2 activators - Screws and fasteners for individual components only

## IMPORTANT INFORMATION

IMPORTANT: Use metric dimensions for greater accuracy during installation. Clamping shoe sold separately. - Please make sure to read the entirety of the installation manual before proceeding with the installation. - Wear safety gear such as gloves, safety glasses, safety shoes, and ear protection. - Every fastener used to attach the track to the wall must be fastened securely into a structural surface. - Always remove debris/dust/residues (sawdust and/or aluminum) from all tracks and guide channels using a dry cloth during installation and before operating the system. - Never spray lubricant on this product. - Do not exceed stated limitations and parameters. This will cause early wear and performance failure, and will void the warranty.

## DISCLAIMER

Pictures provided for visual reference only: actual product may vary. - All required hardware should be ordered and obtained prior to initiating fabrication or installation work. Please verify that the parts and quantities listed in your order are correct before proceeding to checkout. - Always use instructions provided by the manufacturer, as included with the product. Manufacturer reserves the right to amend, modify, or otherwise supplement any previously issued product and/or technical information, as deemed required from time to time, without prior notice. - The documentation, drawings, and instructions on this page apply to the system described on this page only. Richelieu expressly declines all responsibility for any design or construction that combines this system with systems from this same manufacturer or systems from other manufacturers. - Installation of the product shall be executed by qualified individuals only, always ensuring that each product is securely installed using proper fixation methods, as appropriate for each applicable substratum. We trust that anyone installing these products has the required skills, knowledge, and experience. Richelieu expressly disclaims any liabilities for results obtained through improper use or installation.

**PRODUCT PHOTOS**

