



## TERNO CLASSIC 80 BASIC and SYNC

### Detailed Door Movement

Biparting

Single sliding

### Track Mounting

Ceiling Mount

Wall Mount

### Door Thickness

1 3/16 to 1 3/8 in\*

1 3/16 to 1 25/32 in\*

1 3/16 to 2 5/32 in\*

### Overall Length

78 3/4 in\*

98 3/8 in\*

9 ft 10 in\*

13 ft 1 in\*

### Soft-Close Type

2 Shock Absorber

None

### Number of Doors

1

2

### Door Width

23 5/8 to 39 3/8 in\*

23 5/8 to 49 1/4 in\*

23 5/8 to 59 in\*

## DESCRIPTION

### Adjustable

TERNO CLASSIC 80 BASIC and SYNC Series for standard straight sliding wood door system for wood door weight capacities 80 kg each.

#### Features:

- Direct mount suspension bracket to mount to the top of the door
- Select from two types of hardware sets
  - 1) Basic for single doors with standard stops
  - 2) SYNC to synchronize bi parting 2 doors with shock absorber stops
- ADA / Barrier-Free compliant low pull force less than 2.1 kg
- Track options for ceiling mount and wall mount
- Clip-on aluminum anodized fascia options for 35 mm and 45 mm thick doors
- Optional clips for wood fascia supplied by the Contractor

The TERNO CLASSIC 80 BASIC and SYNC Series is an ideal solution for residential and commercial, pocket doors, multi-unit projects, access doors between rooms and room dividers.

**IMPORTANT:** Use metric dimensions for greater accuracy during installation. Groove is required at the bottom of the door, see mounting instructions for details.

Optional two-part floor guide can be purchased separately to avoid cutting a groove.

## ADVANTAGES AND BENEFITS

- Quick, simple, and low-cost installation - Minimal effort required to open door

## AVAILABLE PRODUCTS

Product #	Detailed Door Movement	Track Mounting	Door Thickness	Overall Length	Soft-Close Type	Number of Doors	Door Width
<a href="#">WEBKIT1243936</a>	Biparting	Ceiling Mount	1 3/16 to 2 5/32 in*	13 ft 1 in*	2 Shock Absorber	2	23 5/8 to 39 3/8 in*
<a href="#">WEBKIT1243937</a>	Biparting	Wall Mount	1 3/16 to 1 25/32 in*	13 ft 1 in*	2 Shock Absorber	2	23 5/8 to 39 3/8 in*
<a href="#">WEBKIT1243932</a>	Single sliding	Ceiling Mount	1 3/16 to 1 3/8 in*	78 3/4 in*	None	1	23 5/8 to 39 3/8 in*
<a href="#">WEBKIT1243933</a>	Single sliding	Ceiling Mount	1 3/16 to 2 5/32 in*	98 3/8 in*	None	1	23 5/8 to 49 1/4 in*
<a href="#">WEBKIT1243934</a>	Single sliding	Wall Mount	1 3/16 to 1 3/8 in*	78 3/4 in*	None	1	23 5/8 to 39 3/8 in*
<a href="#">WEBKIT1243935</a>	Single sliding	Wall Mount	1 3/16 to 1 25/32 in*	9 ft 10 in*	None	1	23 5/8 to 59 in*

## TECHNICAL SPECIFICATIONS

Door Material	Wood
Door Movement	Straight Sliding
Roller Position	Upper
Application	Pantry, Standard Access Door, Pocket Door
Brand	Terno
Compatible with	Terno CLASSIC
Adjustable	Yes
Soft-Closing	No
Stopper	Two
Groove Needed for Guiding System	Yes
Door Installation	Top Hung
Door Height	39 3/8 to 106 in*
Brand Model	Terno Classic

### Disclaimer

Measures shown with an asterisk (\*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

## IMPORTANT INFORMATION

**IMPORTANT:** Use metric dimensions for greater accuracy during installation. Groove is required at the bottom of the door, see mounting instructions for details. Optional two-part floor guide can be purchased separately to avoid cutting a groove. - Pictures provided for visual reference only: actual product may vary. - All required hardware should be ordered and obtained prior to initiating fabrication or installation work. Please verify that the parts and quantities listed in your order are correct before proceeding to checkout. - Always use instructions provided by the manufacturer, as included with the product. Manufacturer reserves the right to amend, modify, or otherwise supplement any previously issued product and/or technical information, as deemed required from time to time, without prior notice. - The documentation, drawings, and instructions on this page apply to the system described on this page only. Richelieu expressly declines all responsibility for any design or construction that combines this system with systems from this same manufacturer or systems from other manufacturers. - Installation of the product shall be executed by qualified individuals only, always ensuring that each product is securely installed using proper fixation methods, as appropriate for each applicable substratum. We trust that anyone installing these products has the required skills, knowledge, and experience. Richelieu expressly disclaims any liabilities for results obtained through improper use or installation. - Always remove debris/dust/residues (sawdust and/or aluminum) from all tracks and guide channels using a dry cloth during installation and before operating the system. - Never spray lubricant.

## DISCLAIMER

By accessing or referring to this document, or by using any of Richelieu's websites, you accept all applicable terms as they apply from time to time. This legal disclaimer is in no way limited or altered by any other terms or conditions. Richelieu may change said terms at its discretion and without prior notice. A version of the most current terms will always be available on Richelieu's website. The preceding information and technical documentation, information, or recommendations issued by Richelieu verbally or in writing is believed to be accurate and is given in good faith, but no representation of warranty as to its completeness or accuracy is made. Suggestions for use or application are only opinions. Users are responsible for determining the suitability of these products for their own particular purpose. No representation of warranty, expressed or implied, is made with respect to information or products including, without limitation, warranties or merchantability, fitness for particular purpose, non-infringement of any third party patent or other intellectual property rights including, without limit, copyright, trademark, and designs. Any trademarks identified herein are trademarks of the Richelieu group of companies. Richelieu assumes no risk and shall not be subject to any liability for damages or loss resulting from the specific use or application made of the product. Richelieu's liability for any claim, whether based on breach of contract, negligence, or infringement of any rights of any party relating to the product shall not exceed the price paid for said products. In no event shall Richelieu be liable for any special, incidental, or consequential damages (including loss of use, loss of profit, and claims of third parties) however caused, whether by the negligence of Richelieu or otherwise. Products returned for warranty purposes shall be subject to Richelieu's then applicable Return Policy.

## PRODUCT PHOTOS



