



AVENTOS HL Kits

Door Type

Narrow
Aluminum-
Framed Door
(20 mm and
Less)

Wide
Aluminum-
Framed Door

Wood Door

Door Height

11 3/4 to 13
3/4 in*

13 3/4 to 15
3/4 in*

15 3/4 to 19
5/8 in*

19 3/4 to 22
7/8 in*

Door Weight

2.76 to 4.63
lb*

2.76 to 8.38
lb*

3.86 to 6.83
lb*

4.41 to 10.4
lb*

4.85 to 10.1
lb*

7.05 to 13.7
lb*

8.6 to 15 lb*

10.4 to 18.7
lb*

10.6 to 19.2
lb*

13.9 to 24.5
lb*

15.2 to 25.4
lb*

19 to 31.1 lb*

19 to 31.7 lb*

19.4 to 36.4
lb*

24.7 to 44.1
lb*

25.6 to 44.1
lb*

31.3 to 44.1
lb*

DESCRIPTION

Effortless opening and smooth closing for parallel-opening doors. Designed for doors from 15" to 72" in width and from 11-13/16" to 22-13/16" in height. Easy installation and adjustment. The handle can be installed without any height restrictions.

ADVANTAGES AND BENEFITS

- Integrated BLUMOTION device for soft closing - Parallel opening for complete clearance and ease of access

AVAILABLE PRODUCTS

Product #	Door Type	Door Height	Door Weight
WEBKIT1244220	Narrow Aluminum-Framed Door (20 mm and Less)	11 3/4 to 13 3/4 in*	2.76 to 8.38 lb*
WEBKIT1244225	Narrow Aluminum-Framed Door (20 mm and Less)	11 3/4 to 13 3/4 in*	8.6 to 15 lb*
WEBKIT1244232	Narrow Aluminum-Framed Door (20 mm and Less)	11 3/4 to 13 3/4 in*	15.2 to 25.4 lb*
WEBKIT1244240	Narrow Aluminum-Framed Door (20 mm and Less)	11 3/4 to 13 3/4 in*	25.6 to 44.1 lb*
WEBKIT1244221	Narrow Aluminum-Framed Door (20 mm and Less)	13 3/4 to 15 3/4 in*	2.76 to 4.63 lb*
WEBKIT1244226	Narrow Aluminum-Framed Door (20 mm and Less)	13 3/4 to 15 3/4 in*	4.85 to 10.1 lb*
WEBKIT1244233	Narrow Aluminum-Framed Door (20 mm and Less)	13 3/4 to 15 3/4 in*	10.4 to 18.7 lb*
WEBKIT1244241	Narrow Aluminum-Framed Door (20 mm and Less)	13 3/4 to 15 3/4 in*	19 to 31.1 lb*
WEBKIT1244247	Narrow Aluminum-Framed Door (20 mm and Less)	13 3/4 to 15 3/4 in*	31.3 to 44.1 lb*
WEBKIT1244227	Narrow Aluminum-Framed Door (20 mm and Less)	15 3/4 to 19 5/8 in*	3.86 to 6.83 lb*
WEBKIT1244234	Narrow Aluminum-Framed Door (20 mm and Less)	15 3/4 to 19 5/8 in*	7.05 to 13.7 lb*
WEBKIT1244242	Narrow Aluminum-Framed Door (20 mm and Less)	15 3/4 to 19 5/8 in*	13.9 to 24.5 lb*
WEBKIT1244248	Narrow Aluminum-Framed Door (20 mm and Less)	15 3/4 to 19 5/8 in*	24.7 to 44.1 lb*
WEBKIT1244235	Narrow Aluminum-Framed Door (20 mm and Less)	19 3/4 to 22 7/8 in*	4.41 to 10.4 lb*
WEBKIT1244243	Narrow Aluminum-Framed Door (20 mm and Less)	19 3/4 to 22 7/8 in*	10.6 to 19.2 lb*
WEBKIT1244249	Narrow Aluminum-Framed Door (20 mm and Less)	19 3/4 to 22 7/8 in*	19.4 to 36.4 lb*
WEBKIT1244218	Wide Aluminum-Framed Door	11 3/4 to 13 3/4 in*	2.76 to 8.38 lb*
WEBKIT1244236	Wide Aluminum-Framed Door	11 3/4 to 13 3/4 in*	25.6 to 44.1 lb*
WEBKIT1244223	Wide Aluminum-Framed Door	13 3/4 to 15 3/4 in*	4.85 to 10.1 lb*
WEBKIT1244244	Wide Aluminum-Framed Door	13 3/4 to 15 3/4 in*	31.3 to 44.1 lb*
WEBKIT1244224	Wide Aluminum-Framed Door	15 3/4 to 19 5/8 in*	3.86 to 6.83 lb*
WEBKIT1244245	Wide Aluminum-Framed Door	15 3/4 to 19 5/8 in*	24.7 to 44.1 lb*
WEBKIT1244231	Wide Aluminum-Framed Door	19 3/4 to 22 7/8 in*	4.41 to 10.4 lb*
WEBKIT1244246	Wide Aluminum-Framed Door	19 3/4 to 22 7/8 in*	19.4 to 36.4 lb*
WEBKIT1244222	Wood Door	11 3/4 to 13 3/4 in*	8.6 to 15 lb*
WEBKIT1244228	Wood Door	11 3/4 to 13 3/4 in*	15.2 to 25.4 lb*
WEBKIT1244219	Wood Door	13 3/4 to 15 3/4 in*	2.76 to 4.63 lb*
WEBKIT1244229	Wood Door	13 3/4 to 15 3/4 in*	10.4 to 18.7 lb*
WEBKIT1244237	Wood Door	13 3/4 to 15 3/4 in*	19 to 31.7 lb*
WEBKIT1244230	Wood Door	15 3/4 to 19 5/8 in*	7.05 to 13.7 lb*
WEBKIT1244238	Wood Door	15 3/4 to 19 5/8 in*	13.9 to 24.5 lb*
WEBKIT1244239	Wood Door	19 3/4 to 22 7/8 in*	10.6 to 19.2 lb*

TECHNICAL SPECIFICATIONS

Brand	Blum
Opening Types	Parallel Opening
Minimum internal depth of the enclosure	11 in*

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

APPLICATION

Upper cabinets. Ideal for concealing appliances such as microwaves, and perfectly suited to house items you may occasionally wish to display.

IMPORTANT INFORMATION

For doors with frames less than 22 mm or between 22 and 47 mm in width, we recommend the use of mounting brackets for narrow frames. - For doors more than 1219 mm in width, use two stabilizer rods and one connection piece kit.

PRODUCT PHOTOS



