



Cinetto B-MOVED + PS48 Motorized Sliding Door System

Door Thickness

3/4 to 29/32
in*

15/16 to 1
5/16 in*

Number of Doors

2

3

4

Overall Length

96 in*

11 ft 9 in*

14 ft 6 in*

15 ft 4 in*

19 ft 8 in*

Door Installation

Left and right
hand

Left hand

Right hand

Door Width

35 3/8 to 48
in*

35 3/8 to 49
3/4 in*

45 3/8 to 72
5/8 in*

60 to 60 in*

60 to 60 7/8
in*

DESCRIPTION

UL Listed

The Cinetto B-MOVED + PS48 Motorized bypass sliding door System is designed for two and three-door configurations.

The doors can be moved and controlled hands-free in several ways: push to the door; remote; WAVE proximity sensor (sold separately).

Compatible with Smart Home devices, cellphone AP's, and Voice Control devices (consult a certified electrician). Installation is simple, with a bolt-on motion transmission bar behind the standard PS48 sliding door system.

Three types of bracket sets to link the motion transmission bar to the upper running gear. The control unit is powered by a UL Listed power supply with a standard 3-prong plug for use in a typical North American 120-volt wall outlet.

IMPORTANT: Select the correct motion transmission bar type for the proper door width range. Locate the WAVE sensor within 10 meters (32'-0") from the receiver and sensors. WAVE sensors read through a maximum 10 mm (3/8") thick wood, glass or stone material .

Use metric dimensions for greater accuracy during installation.

Ideal solution for hands-free and barrier-free applications for wardrobes, kitchen pantries, TV & Entertainment Units, and Storage units.

AVAILABLE PRODUCTS

Product #	Door Thickness	Number of Doors	Overall Length	Door Installation	Door Width
WEBKIT1245603	3/4 to 29/32 in*	2	96 in*	Left hand	35 3/8 to 49 3/4 in*
WEBKIT1245602	3/4 to 29/32 in*	2	96 in*	Right hand	35 3/8 to 49 3/4 in*
WEBKIT1245605	3/4 to 29/32 in*	4	15 ft 4 in*	Left and right hand	35 3/8 to 48 in*
WEBKIT1245607	15/16 to 1 5/16 in*	2	11 ft 9 in*	Left hand	45 3/8 to 72 5/8 in*
WEBKIT1245606	15/16 to 1 5/16 in*	2	11 ft 9 in*	Right hand	45 3/8 to 72 5/8 in*
WEBKIT1245608	15/16 to 1 5/16 in*	3	14 ft 6 in*	Left and right hand	60 to 60 in*
WEBKIT1245609	15/16 to 1 5/16 in*	4	19 ft 8 in*	Left and right hand	60 to 60 7/8 in*

TECHNICAL SPECIFICATIONS

Door Material	Wood
Door Movement	Straight Sliding
Detailed Door Movement	Bypassing
Load Capacity	66.1 to 176 lb*
Door Position	Full Overlay
Application	Wardrobe, Pantry, Storage
Brand	CINETTO
Opening	Remote
Brand Model	Cinetto PS48, Cinetto B-Moved

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

IMPORTANT INFORMATION

IMPORTANT: Use metric dimensions for greater accuracy during installation. - When using the B-moved system, refer to a certified electrician before installation to ensure you have a proper power source. - Door width range per transmission bar: Type A: Type B: 2 doors = 900 - 1400 mm 2 doors = 1154 - 1900 mm 3 doors = 1190 - 1400 mm 3 doors = 1523 - 1900 mm - Pictures provided for visual reference only: actual product may vary. - All required hardware should be ordered and obtained prior to initiating fabrication or installation work. Please verify that the parts and quantities listed in your order are correct before proceeding to checkout. - Always use instructions provided by the manufacturer, as included with the product. Manufacturer reserves the right to amend, modify, or otherwise supplement any previously issued product and/or technical information, as deemed required from time to time, without prior notice. - The documentation, drawings, and instructions on this page apply to the system described on this page only. Richelieu expressly declines all responsibility for any design or construction that combines this system with systems from this same manufacturer or systems from other manufacturers. - Installation of the product shall be executed by qualified individuals only, always ensuring that each product is securely installed using proper fixation methods, as appropriate for each applicable substratum. We trust that anyone installing these products has the required skills, knowledge, and experience. Richelieu expressly disclaims any liabilities for results obtained through improper use or installation. - Always remove debris/dust/residues (sawdust and/or aluminum) from all tracks and guide channels using a dry cloth during installation and before operating the system. - Never spray lubricant.

INCLUDED PRODUCT(S)

We strongly recommend that you order the TUBECART and CAP (two CAPs per TUBECART) products to package this product.

DISCLAIMER

By accessing or referring to this document, or by using any of Richelieu's websites, you accept all applicable terms as they apply from time to time. This legal disclaimer is in no way limited or altered by any other terms or conditions. Richelieu may change said terms at its discretion and without prior notice. A version of the most current terms will always be available on Richelieu's website. The preceding information and technical documentation, information, or recommendations issued by Richelieu verbally or in writing is believed to be accurate and is given in good faith, but no representation of warranty as to its completeness or accuracy is made. Suggestions for use or application are only opinions. Users are responsible for determining the suitability of these products for their own particular purpose. No representation of warranty, expressed or implied, is made with respect to information or products including, without limitation, warranties or merchantability, fitness for particular purpose, non-infringement of any third party patent or other intellectual property rights including, without limit, copyright, trademark, and designs. Any trademarks identified herein are trademarks of the Richelieu group of companies. Richelieu assumes no risk and shall not be subject to any liability for damages or loss resulting from the specific use or application made of the product. Richelieu's liability for any claim, whether based on breach of contract, negligence, or infringement of any rights of any party relating to the product shall not exceed the price paid for said products. In no event shall Richelieu be liable for any special, incidental, or consequential damages (including loss of use, loss of profit, and claims of third parties) however caused, whether by the negligence of Richelieu or otherwise. Products returned for warranty purposes shall be subject to Richelieu's then applicable Return Policy.

PRODUCT PHOTOS

