



NEOLOOP - 24 VDC Flexible LED Side-Emitting N1

Kelvin Color Temperature (K)

2700 K

3000 K

3500 K

4800 K

6500 K

DESCRIPTION

Cuttable

Bold lighting for bright applications, achieve consistent, seamless illumination from start to finish with Neoloop, flexible silicone LED lighting. Shatterproof and watertight, side-emitting Neoloop illuminates from the side and bends on a horizontal axis, a perfect solution for adding light to dark millwork, creating unique wall designs, outlining commercial logos and more.

Easily press into a 6 mm W x 12 mm groove for recess mounting or surface mount with U-Clips (sold separately).

Make sure that the wattage of the power supply and/or the control system is always respected during your lighting installations.

On a 24 VDC starter cord, we recommend a maximum linear run of 29.5 ft (9 m).

ADVANTAGES AND BENEFITS

- Durable, flexible silicone construction with a flat illuminated side bendable on the horizontal axis - 3W/ft. *Lunifrom output for continuous illumination - Available in (5) color temperatures: 2700K, 3000K, 3500K, 4800K, 6500K - Sold in 16.4' (5 m and 8 m) rolls and cuttable - Linkable with DIY connectors - no soldering required! - 79" (2 m) Starter Cords are molded on each end for easy installation - Groove for recess mounting or surface mount with U-Clips in indoor, outdoor, damp and wet *Lunifrom : The technology to emilinate "dotted" appearances and reduce unwanted glare within light emitting diode fixtures. **Locations**when used with factory-installed inputs.

AVAILABLE PRODUCTS

Product #	Kelvin Color Temperature (K)
LN124V3WM27K8M	2700 K
LN124V3WM30K8M	3000 K
LN124V3WM35K8M	3500 K
LN124V3WM48K8M	4800 K
LN124V3WM65K8M	6500 K

TECHNICAL SPECIFICATIONS

Location	Furniture, Baseboard, Other
Application	Living Room, Bedroom, Office, Commercial, Furniture, Closet
Mounting	Recessed, Surface
Luminaire	Flexible Linear
Lighting	Ambience
Finish	White
Style	Eclectic
CRI (Color Rendering Index)	90
Luminous Efficiency	33.3 lm/W
Material	Silicone
Power Cable Length	78 3/4 in*
Length	26 ft 2 in*
Height	1/4 in*
Width	15/32 in*
IP	IP65
Lighting Type	LED
Tension (V)	24 V
Watts/Foot	3 W
Features	Cutting distance: 50 mm (1 31/32")
Length of second power cable	78 3/4 in*

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

IMPORTANT INFORMATION

Rated for indoor, outdoor, damp and wet locations. IMPORTANT : When used with factory-installed inputs.

PRODUCT PHOTOS



