



## NEOLOOP - 24 VDC Flexible Top-emitting LED Light N2

### Kelvin Color Temperature (K)

2700 K

3000 K

3500 K

4800 K

6500 K

## DESCRIPTION

### Cuttable

Bold lighting for bright applications, achieve consistent, seamless illumination from start to finish with Neoloop,, flexible silicone LED lighting. Shatterproof and watertight, top-emitting Neoloop illuminates from a curved top and bends on a vertical axis, ideal for architectural accents such as under countertops, soffits or toe kick lighting.

Easily press into a 13/32 in (10 mm) W x 7/16 in (11 mm) groove for recess mounting or surface mount with U-Clips (sold separately).

Make sure that the wattage of the power supply and/or the control system is always respected during your lighting installations.

On a 24 VDC starter cord, we recommend a maximum linear run of 29.5 ft (9 m).

## ADVANTAGES AND BENEFITS

- Durable, flexible silicone construction with a flat illuminated side bendable on the vertical axis - 3W/ft. \*Luniform output for continuous illumination - Available in (5) color temperatures: 2700K, 3000K, 3500K, 4800K, 6500K - Sold in 16.4' (5 m and 8 m) rolls and cuttable - Linkable with DIY connectors - no soldering required! - 79" (2 m) Starter Cords are molded on each end for easy installation - Groove for recess mounting or surface mount with U-Clips in indoor, outdoor, damp and wet \*Luniform : The technology to emilinate "dotted" appearances and reduce unwanted glare within light emitting diode fixtures. \*\*Locations\*\*when used with factory-installed inputs.

## AVAILABLE PRODUCTS

Product #	Kelvin Color Temperature (K)
LN224V3WM27K8M	2700 K
LN224V3WM30K8M	3000 K
LN224V3WM35K8M	3500 K
LN224V3WM48K8M	4800 K
LN224V3WM65K8M	6500 K

## TECHNICAL SPECIFICATIONS

Location	Furniture, Baseboard, Other
Application	Living Room, Bedroom, Office, Commercial, Furniture, Closet
Mounting	Recessed, Surface
Luminaire	Flexible Linear
Lighting	Ambience
Finish	White
Style	Eclectic
CRI (Color Rendering Index)	90
Luminous Efficiency	66.7 lm/W
Material	Silicone
Power Cable Length	78 3/4 in*
Length	5/16 in*
Height	7/16 in*
Width	13/32 in*
IP	IP65
Lighting Type	LED
Tension (V)	24 V
Watts/Foot	3 W
Features	Cutting distance: 50 mm (1 31/32")
Length of second power cable	78 3/4 in*

### Disclaimer

Measures shown with an asterisk (\*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

## IMPORTANT INFORMATION

Rated for indoor, outdoor, damp and wet locations. IMPORTANT : When used with factory-installed inputs.

## PRODUCT PHOTOS



